

[Print](#)

Project Name: AWG_IA_RNAV (GPS) RWY 36, AMDT 1A

Project Reason: CIRCLING CAT B NEW OBSTACLE DATA: 19-054542, TOWER 411806.76N/0914119.91W 943 MSL (1A). OBSTACLE 943 + 300 ROC = 1243 (1260). CIRCLING CAT B MDA/HAA CHANGED FROM 1240/486 TO 1260/506 - NEW OBSTACLE DATA. DELETED NOTE: DME/DME RNP-0.3 NA - REPLACED WITH REQUIREMENT NOTE: RNP APCH. MODIFIED LOCAL ALTIMETER SETTING NOTE BY REMOVING THE "AND ALL VISIBILITIES 1/4 MILES" FROM APV SECTION OF NOTE AND MODIFIED "MILES" TO "SM" PER REVISED FORMAT. MODIFIED ALTERNATE MINIMUMS FROM STANDARD EXCEPT CAT C 800-2 1/4 AND NOTE NA WHEN LOCAL WEATHER NOT AVAILABLE TO STANDARD EXCEPT CAT C 800- 2/1/4, PER .19H PARA 8-6-11B(4) AND 8-6-9F(4) NOTE ONLY REQUIRED WHEN ALTIMETER NOT ON WMSCR, KAWG IS ON WMSCR.

Last Updated By: Deanna Fields

Digitally signed by

Last Updated At: 2019-02-21 16:46:10.955686

DAVID DANNER

Mar 06, 2019

Status: Verified

!FDC 9/9245 AWG IAP WASHINGTON MUNI, Washington, IA. RNAV (GPS) RWY 36, AMDT 1... CIRCLING CAT B MDA1260/HAA 506. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. CHANGE LOCAL ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE IOWA CITY ALTIMETER SETTING: INCREASE LPV DA TO 1064 FEET AND LNAV/VNAV DA TO 1072 FEET; INCREASE ALL MDAS 80 FEET AND VISIBILITY LNAV AND CIRCLING CAT C 1/4 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT C 800-2 1/4. THIS IS RNAV (GPS) RWY 36, AMDT 1A. 1902211646-PERM

