

[Print](#)

Project Name: GPZ - ILS OR LOC RWY 34

Project Reason: DELETED NOTE: NIGHT LANDING: RWY 5 NA AT NIGHT AND ADDED CIRCLING RWY 5 NA DUE TO .19H NOTE FORMAT CHANGE. DELETE ALL REFERENCE TO RWYS 10/28. TURF RWYS NO LONGER EXIST PER AIRNAV PENDING DATA RECORD FOR 4/25/2019. DELETE NOTE: CIRCLING NA TO RWYS 10 AND 28. CHANGE BACKUP ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HIBBING ALTIMETER SETTING: INCREASE DA TO 1624 FEET, INCREASE ALL MDAS 80 FEET AND VISIBILITY S-LOC 34 CATS C/D 1/8 SM AND AND CIRCLING CAT C 1/4 SM DUE TO .19H NOTE FORMAT CHANGE. CHANGE INOP NOTE TO READ: FOR INOPERATIVE ALS, INCREASE S-LOC 34 CATS C/D VISIBILITY TO 1 5/8 SM DUE TO .19H NOTE FORMAT CHANGE. CHANGE INOP NOTE TO READ: FOR INOPERATIVE ALS WHEN USING HIBBING ALTIMETER SETTING, INCREASE S-ILS 34 VISIBILITY TO 3/4 SM DUE TO .19H NOTE FORMAT CHANGE. UPDATED APT ELEV AND TDZE FROM 1355 TO 1356 - NEW SURVEY DATA. UPDATED S-ILS 34 DA FROM 1555 TO 1556 ALL CATS - NEW SURVEY DATA. UPDATED S-LOC 34 HAT FROM 465 TO 464 ALL CATS. UPDATED CIRCLING CAT A, B, C HAA FROM 545 TO 544, AND CAT D HAA FROM 565 TO 564 - NEW SURVEY DATA.

Last Updated By: Sylvan Drakes

Last Updated At: 2019-01-18 13:02:09.099893

Status: Verified

FDC 9/3289

Digitally signed by
WARDELL HENNING
Mar 06, 2019

!FDC X/XXXX GPZ IAP GRAND RAPIDS/ITASCA CO-GORDON NEWSTROM FLD, Grand Rapids, MN. ILS OR LOC RWY 34, AMDT 2A... CHART NOTE: CIRCLING RWY 5 NA AT NIGHT. DELETE NOTE: NIGHT LANDING: RWY 5 NA AT NIGHT. DELETE NOTE: CIRCLING NA TO RWYS 10 AND 28. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HIBBING ALTIMETER SETTING AND INCREASE ALL DA 68 FEET AND ALL MDA 80 FEET. INCREASE S-LOC 34 CATS C/D VISIBILITY 1/8 MILE AND CIRCLING CAT C VISIBILITY 1/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HIBBING ALTIMETER SETTING: INCREASE DA TO 1624 FEET, INCREASE ALL MDAS 80 FEET AND VISIBILITY S-LOC 34 CATS C/D 1/8 SM AND CIRCLING CAT C 1/4 SM. DELETE NOTE: FOR INOPERATIVE MALSR WHEN USING HIBBING ALTIMETER SETTING, INCREASE S-ILS 34 VISIBILITY ALL CATS TO 7/8. CHART NOTE: FOR INOPERATIVE ALS WHEN USING HIBBING ALTIMETER SETTING, INCREASE S-ILS 34 VISIBILITY TO 3/4 SM. DELETE NOTE: FOR INOPERATIVE MALSR, INCREASE S-LOC 34 CATS C/D VISIBILITY TO 1 3/8. CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC 34 CATS C/D VISIBILITY TO 1 5/8 SM. DELETE APT ELEV 1355. CHART APT ELEV 1356. DELETE TDZE 1355. CHART TDZE 1356. S-ILS 34 DA 1556 ALL CATS. S-LOC 34 HAT 464 ALL CATS. CIRCLING CAT A, B, C HAA 544, CAT D HAA 564. THIS IS ILS OR LOC RWY 34, AMDT 2B. 1901181302-PERM

QUALITY
31
CHECKED