

[Print](#)

Project Name: TCY, CA - RNAV (GPS) RWY 26: ADDING ALTERNATE MINIMUMS

Project Reason: KTCY, CA - RNAV (GPS) RWY 26: ADDING ALTERNATE MINIMUMS - 1. CHANGED ALTERNATE MINIMUMS FROM NA TO STANDARD - LOCAL AWOS-3 IS NOW BROADCAST ON WMSCR. 2. CHANGED BACK-UP ALTIMETER SETTING NOTE FROM "WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE STOCKTON ALTIMETER SETTING: INCREASE LPV DA TO 496, LNAV/VNAV DA TO 553; INCREASE ALL MDA 60 FEET AND LPV ALL CATS VISIBILITY 1/4 SM, LNAV/VNAV ALL CATS VISIBILITY 1/8 SM, AND LNAV CAT C VISIBILITY 1/8 SM" TO "WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE STOCKTON ALTIMETER SETTING: INCREASE LPV DA TO 496 FEET, INCREASE LNAV/VNAV DA TO 553 FEET; INCREASE ALL MDAS 60 FEET AND VISIBILITY LNAV CAT C 1/8 SM" - IAW VISCHECK CALCULATOR AND NEW TERMINOLOGY IAW FAAO 8260.19 PARA 8-6-11.

Last Updated By: William Hanby

Last Updated At: 2019-07-11 21:42:08.590712

Status: Verified
9/2673

!FDC ~~XXXXX~~ TCY IAP TRACY MUNI, Tracy, CA. RNAV (GPS) RWY 26, AMDT 1B... CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE STOCKTON ALTIMETER SETTING: INCREASE LPV DA TO 496 FEET, INCREASE LNAV/VNAV DA TO 553 FEET; INCREASE ALL MDAS 60 FEET AND VISIBILITY LNAV CAT C 1/8 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE STOCKTON ALTIMETER SETTING: INCREASE LPV DA TO 496, LNAV/VNAV DA TO 553; INCREASE ALL MDA 60 FEET AND LPV ALL CATS VISIBILITY 1/4 SM, LNAV/VNAV ALL CATS VISIBILITY 1/8 SM, AND LNAV CAT C VISIBILITY 1/8 SM. ALTERNATE MINIMUMS: STANDARD. THIS IS RNAV (GPS) RWY 26, AMDT 1C. 1907112142-PERM

Digitally signed by
CASIMIR L TABAKA
Aug 16, 2019

