

Print

Project Name: AFW RNAV (GPS) RWY 16R

Project Reason: INCREASE THE LPV AND LNAV/VNAV VISIBILITY MINIMUMS TO 1 SM ON RNAV (GPS) RWY 16R APPROACH. NOTES UPDATED TO CURRENT CRITERIA.

Last Updated By: Daniel Weston

Last Updated At: 2024-08-08 16:44:20.123628

Status: Verified 4/5932

Digitally signed by
RAKE MCGRAW
Aug 09, 2024



!FDC X/XXXX AFW IAP PEROT FLD/FORT WORTH ALLIANCE, FORT WORTH, TX. RNAV (GPS) RWY 16R, AMDT 1A...
DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH-GPS. DELETE PROFILE NOTE:
*LNAV ONLY. DELETE ASTERISK FROM MINIMUM ALTITUDE AT DHOBI 2.1 NM TO RW16R 1440. DELETE ASTERISK
FROM VDP AT 1 NM TO RW16R. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS,
LNAV/VNAV NA BELOW -9C OR ABOVE 54C. LPV VIS ALL CATS 1 SM. LNAV/VNAV VIS ALL CATS 1 SM. THIS IS RNAV
(GPS) RWY 16R, AMDT 1B. 2408081644-PERM