

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD TERMINAL ARRIVAL (STAR)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>Arrival Name</u>	<u>Number</u>	<u>STAR Computer Code</u>	<u>Superseded Number</u>	<u>Dated</u>	<u>Effective Date</u>
VANZE (RNAV)	THREE	VANZE.VANZE3	TWO	02/01/2018	

TRANSITION ROUTES:

Transition Name	Transition Computer Code	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	MAA	Crossing Altitude/Fixes
CRAMM	CRAMM.VANZE3	CRAMM	VANZE	285.89	9.60	6000			AT/BELOW FL230
TALLO	TALLO.VANZE3	TALLO	FASON	267.92	32.00	FL180			AT/ABOVE FL240
		FASON	CRAMM	267.55	36.76	10000			AT/BELOW FL230
		CRAMM	VANZE	285.89	9.60	6000			AT/BELOW FL230
WASER	WASER.VANZE3	WASER	ERASE	302.01	15.00	FL180			AT/ABOVE FL240
		ERASE	CRAMM	301.86	35.24	10000			AT/BELOW FL230
		CRAMM	VANZE	285.89	9.60	6000			AT/BELOW FL230

ARRIVAL ROUTE DESCRIPTION:

LANDING SOUTH: RWY 18L/18C/18R: FROM OVER VANZE ON TRACK 286.71/9.05 NM TO MASHH, CROSS MASHH AT/BELOW 16000 AND AT/ABOVE 14000 AT 280 KIAS (MEA 6000), THEN ON TRACK 286.12/12.00 NM TO HLI VORTAC (MEA 6000), THEN ON TRACK 302.55/10.15 NM TO LARUE, CROSS LARUE AT/BELOW 12000 AND AT/ABOVE 10000 AT 250 KIAS (MEA 6000), THEN ON TRACK 302.45/8.14 NM TO FLOND, CROSS FLOND AT/BELOW 11000 AND AT/ABOVE 9000 (MEA 6000), THEN ON TRACK 302.42/2.66 NM TO SUUZE (MEA 6000), THEN ON TRACK 359.92/2.89 NM TO MEBEE, CROSS MEBEE AT/BELOW 10000 AND AT/ABOVE 8000 AT 210 KIAS (MEA 6000), THEN ON TRACK 000.10/4.00 NM TO HADSO, CROSS HADSO AT/BELOW 8000 AND AT/ABOVE 6000 (MEA 4000), THEN ON TRACK 000.01/13.61 NM TO HEXIN, CROSS HEXIN AT 3000 (MEA 3000) THEN ON TRACK 000.01. EXPECT RADAR VECTORS TO FINAL APPROACH COURSE.
LANDING NORTH: RWY 36L/36C/36R/9/27: FROM OVER VANZE ON TRACK 284.20/11.00 NM TO CHLMR, CROSS CHLMR AT 10000 AT 230 KIAS (MEA 6000), THEN ON TRACK 284.20. EXPECT RADAR VECTORS TO FINAL APPROACH COURSE.

PBN REQUIREMENT NOTES:

RNAV 1 - DME/DME/IRU OR GPS REQUIRED

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED

PROCEDURAL DATA NOTES:

NOTE: DESCEND VIA MACH NUMBER UNTIL TRANSITION TO 290 KIAS.
NOTE: JET AIRCRAFT ONLY.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD TERMINAL ARRIVAL (STAR)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>Arrival Name</u>	<u>Number</u>	<u>STAR Computer Code</u>	<u>Superseded Number</u>	<u>Dated</u>	<u>Effective Date</u>
VANZE (RNAV)	TREE	VANZE.VANZE3	TWO	02/01/2018	

NOTE: EXPECT TO RECEIVE LANDING DIRECTION (NORTH/SOUTH) AND "DESCEND VIA" CLEARANCE FROM MEMPHIS CENTER , MEMPHIS APPROACH WILL ASSIGN LANDING RUNWAY.

NOTE: LANDING SOUTH INDICATES RWY 18L/18C/18R.

NOTE: LANDING NORTH INDICATES RWY 36L/36C/36R/9/27.

CHART: CROSS ERASE, FASON, AND CRAMM AT 290 KIAS. CHART: CROSS VANZE AT 280 KIAS.

CHART AT HEXIN: "LANDING SOUTH: RWY 18L/18C/18R: EXPECT RADAR VECTORS TO FINAL APPROACH COURSE AFTER HEXIN."

CHART AT CHLMR: "LANDING NORTH: RWY 36L/36C/36R/9/27: EXPECT RADAR VECTORS TO FINAL APPROACH COURSE AFTER CHLMR."

FIXES AND/OR HOLDING PATTERNS:

CHART HOLDING PATTERNS: FASON (HOLD E, RT, 267.55 INBOUND, 15 NM LEGS); ERASE (HOLD SE, RT, 301.86 INBOUND, 15 NM LEGS); CRAMM (HOLD E, RT, 285.89 INBOUND, 15 NM LEGS); LARUE (HOLD SE, RT, 302.45 INBOUND, 6 NM LEGS).

COMMUNICATIONS:

CHART: MEM APP CON

AIRPORTS SERVED

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
MEMPHIS INTL (KMEM)	MEMPHIS	TN

LOST COMMUNICATIONS PREFERENCES:

REMARKS:

REQUEST NOTE "DESCEND VIA MACH NUMBER UNTIL TRANSITION TO 290 KIAS" BE LISTED FIRST IN CHART NOTES. VANZE ABBREVIATED AMENDMENT DOES NOT SATISFY PERIODIC REVIEW REQUIREMENTS.

ADDITIONAL FLIGHT DATA:

DME/DME ASSESSMENT: SAT (RNP 2.0).

REFERENCE MAGVAR: KMEM 1W/2020.

FLIGHT INSPECTED BY:

ORGANIZATION:

DATE:

Processed IAW Technical Support Group (AJF-17) Memo dated 07/07/2021 Guidance for Procedural Changes Requiring Flight Inspection/Validation

Flight Inspected Signature:

Digitally signed by

DAVID DANNER

Mar 01, 2022

DEVELOPED BY:

JOSEPH L. ZEDER

AJV-A442

Developed By Signature:

Digitally signed by

JOSEPH L ZEDER

APPROVED BY:

PATRICK MULQUEEN

AJV-A440

Approved By Signature:

Feb 04, 2022

Digitally signed by

DAVID DANNER

Mar 01, 2022

CHANGES:



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD TERMINAL ARRIVAL (STAR)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>Arrival Name</u>	<u>Number</u>	<u>STAR Computer Code</u>	<u>Superseded Number</u>	<u>Dated</u>	<u>Effective Date</u>
VANZE (RNAV)	THREE	VANZE.VANZE3	TWO	02/01/2018	

- 1. CHANGED FIX NAME FASOP TO CHLMR, FIX MAINTAINED THE SAME LOCATION
- 2. REMOVED RECOMMENDED NAVAID.
- 3. NOTES: TURBOJET AIRCRAFT CHANGED TO JET AIRCRAFT.

REASONS:

- 1. ADDRESS PILOT CONFUSION WITH SIMILAR SOUNDING FIX. NO TRACK OR ALTITUDE CHANGES.
- 2. NO LONGER REQUIRED.
- 3. IAW 8260.19I DOCUMENTATION STANDARDS.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STAR (DATA RECORD)**

Arrival Name				Number			STAR Computer Code		Superseded Number		Dated	Effective Date
VANZE (RNAV)				THREE			VANZE.VANZE3		TWO		02/01/2018	
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS			
EN ROUTE TRANSITION												
CRAMM	343811.05N/0885354.88W	Y		IF			AT/BELOW FL230	290K	CRAMM.VANZE3			
VANZE	344038.74N/0890509.72W	Y	FB	TF	284.89	9.60	AT/BLEOW FL230	280K				
EN ROUTE TRANSITION												
TALLO	344221.47N/0873042.38W	Y		IF					TALLO.VANZE3			
FASON	344031.98N/0880926.98W	Y	FB	TF	266.92	32.00	AT/ABOVE FL240	290K				
CRAMM	343811.05N/0885354.88W	Y	FB	TF	266.55	36.76	AT/BELOW FL230	290K				
VANZE	344038.74N/0890509.72W	Y	FB	TF	284.89	9.60	AT/BELOW FL230	280K				
EN ROUTE TRANSITION												
WASER	341226.54N/0880143.83W	Y		IF					WASER.VANZE3			
ERASE	342010.02N/0881715.32W	Y	FB	TF	301.01	15.00	AT/ABOVE FL240	290K				
CRAMM	343811.05N/0885354.88W	Y	FB	TF	300.86	35.24	AT/BELOW FL230	290K				
VANZE	344038.74N/0890509.72W	Y	FB	TF	284.89	9.60	AT/BELOW FL230	280K				
RUNWAY TRANSITION												
VANZE	344038.74N/0890509.72W	Y		IF			AT/BELOW FL230	280K				

QUALITY

16



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STAR (DATA RECORD)**

Arrival Name	Number	STAR Computer Code	Superseded Number	Dated	Effective Date
VANZE (RNAV)	THREE	VANZE.VANZE3	TWO	02/01/2018	

FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
CHLMR	344309.05N/0891809.21W	Y	FO	TF	283.20	11.00	AT 10000	230K	
RWY 36L/36C/36R, 9,27				FM	283.20				
RUNWAY TRANSITION									
VANZE	344038.74N/0890509.72W	Y		IF			AT/BELOW FL230	280K	
MASHH	344305.51N/0891543.70W	Y	FB	TF	285.71	9.05	AT/BELOW 16000 AT/ABOVE 14000	280K	
HLI VORTAC	344612.88N/0892947.47W	Y	FB	TF	285.12	12.00			
LARUE	345131.48N/0894017.81W	Y	FB	TF	301.55	10.15	AT/BELOW 12000 AT/ABOVE 10000	250K	
FLOND	345546.38N/0894844.51W	Y	FB	TF	301.45	8.14	AT/BELOW 11000 AT/ABOVE 9000		
SUUZE	345709.67N/0895130.14W	Y	FB	TF	301.42	2.66			
MEBEE	350003.36N/0895134.12W	Y	FB	TF	358.92	2.89	AT/BELOW 10000 AT/ABOVE 8000	210K	
HADSO	350403.72N/0895138.69W	Y	FB	TF	359.10	4.00	AT/BELOW 8000 AT/ABOVE 6000		
HEXIN	351741.61N/0895155.91W	Y	FO	TF	359.01	13.61	AT 3000		
RWY 18L/18C/18R				FM	359.01				

