

[Print](#)

Project Name: KGSH NEW CIRCLING RADII APPLIED

Project Reason: Expanded circling area applied. Alternate minimums and secondary altimeter notes updated as required. Only circling visibility verified. Incorporated 0/6796 into the ILS or LOC RWY 27. Controlling obstacles: CAT A: 982 POLE (18-030503) 413141.17N/0854530.15W (1A). 982+300(ROC)=1300 MDA/HAA 473. CAT B: 1002 TOWER (18-002640) 413008.61N/0854957.39W (1A)/ 1002+300(ROC)=1320 MDA/HAA 493. CAT C: 1143 TOWER (18-001641) 413229.00N/0855106.00W (5D). 1143+300(ROC)+50(AC)=1500 MDA/HAA 673. CAT D: 1230 AAO 412752.76N/0854917.51W (2C). 1230+30(ROC)=1540 MDA/HAA 713. Radii: CAT A: 1.30, CAT B:1.83, CAT C: 2.88, CAT D: 3.77. Order 8260.3, chapter 2, New Circling Criteria Applied.

Last Updated By: James Lafferty

Last Updated At: 2021-02-24 15:18:35.799499

Status: Draft

1/0941

!FDC X/XXXX GSH IAP GOSHEN MUNI, GOSHEN, IN. ILS OR LOC RWY 27, AMDT 1A... CEDOB FIX MINIMUMS: S-LOC 27 VIS CAT C 1 3/8. CIRCLING CAT C MDA 1500/HAA 673, CIRCLING CAT D MDA 1540/HAA 713, VIS CAT C 2, VIS CAT D 2 1/4. CEDOB FIX MINIMUMS: CIRCLING CAT B MDA 1320/HAA 493. CIRCLING CAT C MDA 1500/HAA 673, CIRCLING CAT D MDA 1540/HAA 713, VIS CAT C 2, VIS CAT D 2 1/4. CHANGE NOTE TO READ: CIRCLING NA TO RWYS 5 AND 23. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WARSAW ALTIMETER SETTING; INCREASE DA TO 1067 FEET AND ALL MDAS 40 FEET; INCREASE S-LOC 27 CATS C/D VISIBILITY 1/8 SM AND ALL CIRCLING CAT D VISIBILITIES 1/4 SM. THIS IS ILS OR LOC RWY 27, AMDT 1B. 2102241518-PERM

Digitally signed by
DAVID TEFFETELLER
Mar 04, 2021

