

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
HENRY	FOUR	HENRY4.PHF	THREE	05/26/2016	

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

DP ROUTE DESCRIPTION:

TAKEOFF RWY 2: CLIMB ON HEADING 021.80 TO 2000, THENCE...

TAKEOFF RWY 7: CLIMB ON HEADING 066.80 TO 2000, THENCE...

TAKEOFF RWY 20: CLIMBING RIGHT TURN TO 2000 ON HEADING 250.00, THENCE...

TAKEOFF RWY 25: CLIMB ON HEADING 246.81 TO 2000, THENCE...

...ON VECTORS TO ASSIGNED ROUTE/FIX. EXPECT REQUESTED ALTITUDE TEN MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
-------------------------------	--	-----------------------------------	---------------------------------	----------------------	------------------------	-------------------	--------------------	---

PBN REQUIREMENT NOTES:

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED

PROCEDURAL DATA NOTES:

TAKEOFF MINIMUMS:

RWY 2, 7, 20, 25, STANDARD.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

MSA:

FROM ORF VORTAC 360-090 1800, 090-360 2300



LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:
AIRPORT MAGVAR: PHF W09/1985

AIRPORTS SERVED:			
AIRPORT ID	CITY		STATE
PHF	NEWPORT NEWS		VA

COMMUNICATIONS:
CHART: ATIS, CLNC DEL, GND CON, TOWER, DEP CON

FIXES AND/OR NAVAIDS:
JAMIE, WAIKS, FAK VORTAC, HCM VORTAC, HPW VORTAC, ORF VORTAC.

REMARKS:
ABBREVIATED AMENDMENT.
TOP ALTITUDE NOT PUBLISHED PER ATC REQUEST.

FLIGHT INSPECTED BY	SIGNATURE	Digitally signed by	OFFICE	DATE
PROCESSED IAW TECHNICAL SUPPORT GROUP (AJF-17) MEMO DATED 07/07/2021 GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION.	ROBERT G HAMILTON			
		Apr 08, 2025		

DEVELOPED BY	SIGNATURE	Digitally signed by	OFFICE	DATE
PHILLIP G. SMART	ROBERT G HAMILTON		AJV-A433	12/30/2024
		Apr 08, 2025		

APPROVED BY	SIGNATURE	Digitally signed by	OFFICE	DATE	TITLE
ROBERT HAMILTON	ROBERT G HAMILTON				
		Apr 08, 2025			

REQUIRED EFFECTIVE DATE	
ROUTINE	Apr 08, 2025

COORDINATED WITH:

A4A ☐ ALPA ☒ AOPA ☒ APA ☒ HAI ☐ NBAA ☒ OTHER:ORF APP CON, ORF ATCT, AMGR, ZDC

CHANGES - REASONS:
1. REMOVED CCV VORTAC, SBY VORTAC, AND SWL VORTAC FROM FIXES AND/OR NAVAIDS - NAVAIDS SCHEDULED TO BE DECOMISSIONED
2. UPDATED TAKEOFF OBSTACLE NOTES: SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP) - 8260.46J

