

[Print](#)

Project Name: RYV - NEW CIRCLING CRITERIA APPLIED

Project Reason: Project Reason: NEW CIRCLING RADII: CAT A: 1.30, CAT B: 1.83, CAT: 2.88 AND CAT D 3.77. CONTROLLING OBSTACLE CAT A 1020 MSL 55-001537 TANK 431115.00N/0884234.00W (4D), OBS 1020 + ROC 300 + AC 50 = 1370 (1380). CONTROLLING OBSTACLE CAT B 1083 MSL 55-001989 TOWER 431130.90N/0884509.10W (4D), OBS 1083 + ROC 300 + AC 50 = 1433 (1440). CONTROLLING OBSTACLE CAT C 1359 MSL TOWER 55-000798 431143.00N/0884517.00W (5D), OBS 1359 + ROC 300 + AC 50 = 1709 (1720). CAT D CIRCLING: CONTROLLING OBSTACLE CAT D 1359 MSL TOWER 55-000798 431143.00N/0884517.00W (5D), OBS 1359 + ROC 300 + AC 50 = 1709 (1720). UPDATED NOTES AND ALTERNATE MINIMUMS AS REQUIRED. Order 8260.3, chapter 2, New Circling Criteria Applied.

Last Updated By: Brett Cannon

Last Updated At: 2021-06-09 15:04:48.447887

1/8244

Status: Verified

!FDC X/XXXX RYV IAP WATERTOWN MUNI, WATERTOWN, WI. RNAV (GPS) RWY 5, ORIG-A... CIRCLING CAT C MDA 1720/HAA 887. CIRCLING CAT C VIS 2 3/4. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE DODGE COUNTY ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET, INCREASE LNAV CAT C VISIBILITY 1/8 SM. ALTERNATE MINIMUMS: STANDARD; EXCEPT CAT C 900-2 3/4, CAT D 900-3; NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 5, ORIG-B. 2106091504-PERM

Digitally signed by  
**DAVID TEFFETELLER**  
Jun 22, 2021

