

[Print](#)

Project Name: KSAV RNAV (GPS) RWY 10

Project Reason: (1) CHANGE LVAV/VNAV DA/HAT FROM 507/474 TO 530/500 DUE TO NEW CONTROLLING OBSTACLE, 170 SIGN (13-101773) 320809.91N/0811427.41W AC 4D. (2) CHANGE LNAV CAT D VISIBILITY FROM RVR 4000 TO RVR 5000. (3) CHANGE BARO-VNAV NOTE FROM For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 49°C (120°F) TO FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV BELOW -15°C OR ABOVE 54°C. (4) CHANGED BACKUP ALTIMETER NOTE FROM When local altimeter setting not received, use Hilton Head Island, SC altimeter setting and increase all DA 65 feet and all MDA 80 feet and LNAV/VNAV all CATS and circling CATS C/D visibilities 1/4 mile TO WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HILTON HEAD ISLAND ALTIMETER SETTING AND INCREASE LPV DA TO 296 FEET AND ALL VISIBILITIES TO RVR 2000, INCREASE LNAV/VNAV DA TO 596 FEET AND ALL VISIBILITIES TO 1 1/4 SM, INCREASE ALL MDAS 80 FEET AND LNAV CAT C/D VISIBILITY TO RVR 5000. (5) CHANGED INOPERATIVE LIGHTING NOTE FROM for inoperative MALS when using Hilton Head Island altimeter setting, increase LPV all CATS visibility to RVR 5000 TO CHART NOTE: FOR INOPERATIVE ALS WHEN USING HILTON HEAD ISLAND ALTIMETER SETTING, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 5/8 SM. INCREASE LNAV CAT C/D VISIBILITY TO 1 5/8 SM. (6) UPDATED PBN REQUIREMENT NOTE. (7) FOR INOPERATIVE ALS WHEN USING HILTON HEAD ISLAND ALTIMETER SETTING, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 5/8 SM, INCREASE LNAV CAT C/D VISIBILITY TO 1 3/8 SM. (8) ADDED CHART NOTE: FOR INOPERATIVE ALS INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 3/8 SM, INCREASE LNAV CAT C/D TO RVR 6000. (9) DELETED *LNAV ONLY, (10) DELETED ASTERISK ASTERISK LPV DA 1800, (11) DELETED ASTERISK FROM VDP AT 1.1 NM TO RWY 10. (12) UPDATED ALTERNATE MINIMUMS.

Last Updated By: WILLIAM MELTON

Last Updated At: 2022-05-24 12:26:55.627746

Status: Draft



IFDC 2/3428 SAV IAP SAVANNAH/HILTON HEAD INTL, SAVANNAH, GA. RNAV (GPS) RWY 10, AMDT 2B... LPV VIS RVR 1800 ALL CATS. LNAV/VNAV DA 530/HAT 500, ALL CATS VIS RVR 5000. LNAV CAT D VIS RVR 4000.. DELETE NOTE:**RVR 1800 ALL CATS, RVR 2000 WHEN USING HILTON HEAD ISLAND, SC ALTIMETER SETTING. DELETE ASTERISK, ASTERISK LPV DA. DELETE ASTERISK FROM VDP AT 1.1 NM TO RWY 10. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15°C OR ABOVE 54°C. DELETE NOTE: DME/DME RNP-0.3 NA. CHANGE NOTE TO READ: FOR INOPERATIVE ALS INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 3/8 SM, INCREASE LNAV CAT C/D TO RVR 6000. CHANGE NOTE TO READ: FOR INOPERATIVE ALS WHEN USING HILTON HEAD ISLAND ALTIMETER SETTING, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 5/8 SM, INCREASE LNAV CAT C/D VISIBILITY TO 1 3/8 SM. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HILTON HEAD ISLAND ALTIMETER SETTING AND INCREASE LPV DA TO 296 FEET AND ALL VISIBILITIES TO RVR 2000, INCREASE LNAV/VNAV DA TO 596 FEET AND ALL VISIBILITIES TO 1 1/4 SM, INCREASE ALL MDAS 80 FEET AND LNAV CAT C/D VISIBILITY TO RVR 5000. PBN REQUIREMENTS: RNP APCH - GPS. ALTERNATE MINIMUMS: STANDARD - NA WHEN LOCAL WEATHER NOT AVAILABLE. DELETE *LNAV ONLY. THIS IS RNAV (GPS) RWY 10, AMDT 2C. 2205241226-PERM

Digitally signed by

ALLAN WILL

Jun 03, 2022