

Print

Project Name: GVT - CIRCLING ICON

Project Reason: Updated 2/7/22 (D Sickels): Order 8260.3, Chapter 2, new circling criteria applied based on RNAV (GPS) Rwy 17 that already has expanded circling. Only circling mins verified. Circling controlling obstacles - Cat A/B 681 ATCT (48-093499) 330400.52N / 0960413.07W (1A) 681 + 300 = 981 (1000), Cat C 755 Tower 330412.49N / 0960643.87W (1A) 755 + 300 = 1055 (1060), Cat D 922 Tower 330644.92N / 0960738.67W (2C) 922 + 300 = 1222 (1240), Cat E 932 Tower 330803.41N / 0960736.00W (5D) 932 + 50 + 300 = 1282 (1300), Radii Cat A 1.30, Cat B 1.82, Cat C 2.87, Cat D 3.74, Cat E 4.68.

Last Updated By: DALE SICKELS

Last Updated At: 2022-02-07 20:17:12.966212

Status: Verified **2/8888**

QUALITY
47
CHECKED

IFDC X/XXXX GVT IAP MAJORS, GREENVILLE, TX. RNAV (GPS) RWY 35, AMDT 1... CIRCLING CAT C MDA 1060/HAA 525, CAT D MDA 1240/HAA 705, CAT E MDA 1300/HAA 765, VIS CAT D 2 1/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TERRELL ALTIMETER SETTING: INCREASE ALL MDA 80 FEET AND VISIBILITY LNAV AND CIRCLING CATS C, D, AND E 1/4 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4, CAT E 800-2 3/4; NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 35, AMDT 1A. 2202072017-PERM

Digitally signed by
JASON KRETSCHMER
Feb 28, 2022