

[Print](#)

Project Name: GRB ILS OR LOC RWY 36 P-NOTAM

Project Reason: PR IDENTIFIED HIGHER MINIMUMS FOR CIRC CAT C/D USING INCREASED CIRCLING RADII WHEN NOT PUBLISHED ON PROCEDURE. LOC FINAL OBSTACLES UPDATED CONCURRENTLY. LOC FINAL OBST: AAO 442423.58N/0880640.36W, 859 MSL/200 AGL, 2C AC, 250 ROC, 91 DG, 1200 MDA/516 HAT. LOC FINAL S/D OBST: GRAIN_ELEVATOR (55-088338) 442731.21N/0880815.87W, 762 MSL, 1A AC, 250 ROC, 1020 MDA/336 HAT. CIRCLING CAT A/B OBST: TREE 443049.00N/0880641.00W, 869 MSL, 2C AC, 300 ROC, 31 XP, 1200 MDA/505 HAA. CIRCLING CAT C OBST: TOWER (55-081763) 443004.42N/0881127.67W, 935 MSL, 4D AC, 300 ROC, 50 AC, 1300 MDA/605 HAA. CIRCLING CAT D OBST: STACK (55020332) 442931.41N/0880153.17W, 989 MSL, 1A AC, 300 ROC, 1300 MDA/605 HAA. CHANGES AND REASONS: 1. INCREASED S-LOC 36 MAZTT FIX MINS FROM 980 TO 1020 - NEW FINAL CONTROLLING OBSTACLE. 2. INCREASED CIRCLING AND MAZTT FIX MINS CIRCLING CATS C/D MDA FROM 1200 TO 1300 - NEW CONTROLLING OBSTACLE AFTER APPLYING NEW CIRCLING CRITERIA. 3. CHARTED NEW FAS OBST AND CHANGED MAZTT LOC FINAL OBST FROM 739 TREES TO 762 GRAIN ELEVATOR - OBSTACLE EVAL IDENTIFIED NEW CONTROLLER. 4. INCREASED CIRCLING AND MAZTT FIX MINS CIRCLING CAT C VIS FROM 1 1/2 TO 1 3/4 - VIS CK TOOL. 5. CHANGED S-LOC 36 CATS C/D VIS FROM RVR 5000/6000 TO 5500 - VIS CK TOOL. 6. CHANGED MAZTT FIX MINS S-LOC 36 CATS C/D VIS FROM RVR 2400/4000 TO 2600 - VIS CK TOOL. 7. REPLACED INOPERATIVE MALSR NOTE WITH INOPERATIVE ALS NOTE CHANGING VIS ADJUSTMENT FROM "CAT D TO RVR 5000: TO READ "CATS C/D VIS TO 1 3/8" - VIS CK TOOL. 8. CHARTED CIRCLING ICON - APPLIED NEW CIRCLING CRITERIA. CIRCLING RADII: CAT A=1.30, CAT B=1.83, CAT C=2.88, CAT D=3.76

Last Updated By: KELLY DEAN

Last Updated At: 2021-03-09 20:42:14.856229

Digitally signed by
DONALD H LANIER
Apr 26, 2021

Status: Verified FDC 1/5514

!FDC X/XXXX GRB IAP GREEN BAY-AUSTIN STRAUBEL INTL, GREEN BAY, WI. ILS OR LOC RWY 36, AMDT 9A... S-LOC 36 CATS C/D VIS RVR 5500. CIRCLING CATS C/D MDA 1300/HAA 605, VIS CAT C 1 3/4. CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC 36 CATS C/D VISIBILITY TO 1 3/8 SM. DELETE NOTE: FOR INOPERATIVE MALSR, INCREASE S-LOC 36 MAZTT FIX MINIMUMS CAT D VISIBILITY TO RVR 5000. MAZTT FIX MINIMUMS: S-LOC 36 MDA 1020/HAT 336 ALL CATS, VIS CATS C/D RVR 2600. CHART CIRCLING ICON. CHART FAS OBST: 762 GRAIN ELEVATOR (55-088338) 442731N/0880816W. THIS IS ILS OR LOC RWY 36, AMDT 9B. 2103092042-PERM

QUALITY
8
CHECKED