

[Print](#)

Project Name: TTF - NEW CIRCLING AREA

Project Reason: ORDER 8260.3, CHAPTER 2, NEW CIRCLING CRITERIA APPLIED. ONLY CIRCLING EVALUATED. ALL OTHER PORTIONS OF PROCEDURE EVALUATED "AS PUBLISHED". CIRCLING OBSTRUCTIONS: CAT A: 760 TOWER (26-002897) 415506.81N/0832613.53W (2C) 760+300=1060 CAT B: 795 TOWER (26-002922) 415731.00N/0832340.00W (4D) 795+300+AC50=1145 ROUNDED TO 1160. CAT C/D: 1013 TOWER (26-000288) 415328.00N/0832540.00W (4D) 1013+300+AC50=1363 ROUNDED TO 1380. CIRCLING VIS CHECKS VIA TARGETS RS: 1, 1, 2 1/4, 2 1/2. ALTERNATE ALTIMETER NOTE REQUIRES UPDATE. ALTERNATE MINIMUMS REQUIRE UPDATE. RADII: 1.30, 1.83, 2.87, 3.75. UPDATE PBN REQUIREMENTS NOTE TO RNP APCH-GPS. RWY 21: UPDATE BARO/VNAV NOTE TO REMOVE F DESIGNATIONS. CHART NOTE: CIRCLING RWY 3 NA AT NIGHT. 20:1S FOUND ON RWY 3 PROCEDURE. RWY 3: CHANGE NOTE: FROM STRAIGHT IN RWY 3 NA AT NIGHT TO PROCEDURE NA AT NIGHT. 20:1S FOUND ON PROCEDURE.

Last Updated By: Ralph Miller

Last Updated At: 2022-08-08 12:29:47.739871

Status: Verified **2/3573**

IFDC X/XXXX TTF IAP CUSTER, MONROE, MI. RNAV (GPS) RWY 21, ORIG-A... CIRCLING CAT C/D MDA 1380/HAA 764. CIRCLING VISIBILITY CAT C 2 1/4, CAT D 2 1/2. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE DETROIT METRO WAYNE COUNTRY ALTIMETER SETTING: INCREASE LPV DA TO 1011 FEET; INCREASE LNAV/VNAV DA TO 1054 FEET; INCREASE ALL MDAS 60 FEET AND VISIBILITY LNAV CAT C AND CIRCLING CAT C/D 1/4 SM. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16°C OR ABOVE 47°C. CHART NOTE: CIRCLING TO RWY 3 NA AT NIGHT. DELETE PBN REQUIREMENTS NOTE: RNP APCH. PBN REQUIREMENTS NOTE: RNP APCH-GPS. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT C 800-2 1/4, CAT D 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 21, ORIG-B. 2208081229-PERM

Digitally signed by
JASON KRETSCHMER
Aug 19, 2022

