

[Print](#)

Project Name: KMYJ NEW CIRCLING RADII APPLIED

Project Reason: Expanded circling area applied. Updated secondary altimeter setting notes as required and corrected the RASS adjustment from 121 feet to 74 feet. Controlling obstacles: CAT A/B: 969 TOWER (29-002962) 391036.08N/0914742.54W (2C). 969+300(ROC)=1280 MDA. CAT C: 1055 TOWER (29-000624) 391128.00N/0915202.00W (4D). 1055+300(ROC)+50(AC)=1420 MDA. Radii: CAT A: 1.30, CAT B: 1.83, CAT C: 2.88. Order 8260.3, chapter 2, New Circling Criteria Applied.

Last Updated By: James Lafferty

Last Updated At: 2021-05-17 10:37:02.901367 1/8022

Status: Draft

!FDC X/XXXX MYJ IAP MEXICO MEML, MEXICO, MO. RNAV (GPS) RWY 6, AMDT 1B... CIRCLING CAT C MDA 1420/HAA 597. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE COLUMBIA RGNL ALTIMETER SETTING; INCREASE LPV DA TO 1147 FEET AND VISIBILITY ALL CATS 1/8 SM; INCREASE LNAV/VNAV DA TO 1173 FEET AND VISIBILITY ALL CATS 1/8 SM; INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C 3/8 SM AND CIRCLING VISIBILITY CAT C 1/2 SM. THIS IS RNAV (GPS) RWY 6, AMDT 1C. 2105171037-PERM

Digitally signed by
DAVID TEFFETELLER
May 19, 2021

QUALITY
45
CHECKED