

[Print](#)

Project Name: FFM NEW CIR RADII

Project Reason: ORDER 8260.3, CHAPTER 2, NEW CIRCLING CRITERIA APPLIED: CATEGORY RADII: CAT A: 1.31, CAT B: 1.85, CAT C: 2.91 AND CAT D: 3.80. CONTROLLING OBSTACLE CAT A 1339 MSL TOWER (27-002498) 461739.33N/0960735.38W (2C), OBS 1339 + ROC 300 = 1639 (1640). CONTROLLING OBSTACLE CAT B 1440 MSL TREE 461701.68N/0960625.74W (2C), OBS 1440 + ROC 300 = 1740. CONTROLLING OBSTACLE CAT C 1453 MSL TRANSMISSION LINE (27-026280) 461835.14N/ 0960718.93W (5D), OBS 1453 + ROC 300 + AC 50= 1803 (1820). CONTROLLING OBSTACLE CAT D 1637 MSL TOWER (27-000571) 461910.00N/0960536.00W (2C), OBS 1637 + ROC 300 = 1937 (1940). RNAV GPS RWY 35 FINAL AND FAS OBS: CONTROLLING OBSTACLE 1308 MSL TOWER (27-087668) 461211.23N/0960844.22W (1A), OBS 1308 + ROC 250, = 1558 (1560). UPDATED SECONDARY ALTIMETER TO ELBOW LAKE. UPDATED NOTES, VISIBILITIES AND ALTERNATE MINIMUMS WHERE REQUIRED.

Last Updated By: Andre Marsh

Last Updated At: 2021-03-11 15:41:03.001066

Status: Verified **1/4359**

IFDC X/XXXX FFM IAP FERGUS FALLS MUNI-EINAR MICKELSON FLD, FERGUS FALLS, MN. ILS OR LOC RWY 31, AMDT 2... CIRCLING CAT C MDA 1820/HAA 637, CAT D MDA 1940/HAA 757, CAT C VIS 1 3/4, CAT D VIS 2 1/2. DELETE PLANVIEW NOTE: ADF OR DME REQUIRED. CHART EQUIPMENT REQUIREMENTS NOTE: ADF OR DME REQUIRED. CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ELBOW LAKE ALTIMETER SETTING AND INCREASE DA TO 1428 AND ALL MDAS 60 FEET; INCREASE S-LOC CAT C/D VISIBILITY 1/8 SM AND CIRCLING CAT C/D VISIBILITY 1/4 SM. DELETE NOTE: FOR INOPERATIVE MALSR WHEN USING WHEATON ALTIMETER SETTING, INCREASE S-ILS 31 ALL CATS VISIBILITIES 1/2 MILE. ALTERNATE MINIMUMS: ILS STANDARD, NA WHEN LOCAL WEATHER NOT AVAILABLE. LOC STANDARD EXCEPT CAT D 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS ILS OR LOC RWY 31, AMDT 2A. 2103111541-PERM

Digitally signed by
JASON KRETSCHMER
Mar 17, 2021

