

[Print](#)

Project Name: KDKB RNAV GPS RWY 2 - NEW CIRCLING RADII

Project Reason: New circling areas established. Controlling obstacles: Cat A: TOWER (17-002620) 415705.59N/0884315.55W, 1054, 2C (maintained previous minimums). 1054 + 300 (ROC) = 1360 MDA. Cat B: TOWER (17-000133) 415444.54N/0914238.00W, 1185, 2C (new). 1185 + 300 (ROC) = 1500 MDA. Cat C: TOWER (17-000415) 415837.82N/0884347.76W, 1237, 4D (new). 1237 + 300 (ROC) + 50 (AC) = 1600 MDA. Cat D: TOWER (17-001173) 415837.82N/0884347.76W, 1287, 5D (new). 1383 + 300 (ROC) + 50 (AC) = 1740 MDA. Radii: Cat A: 1.30, Cat B: 1.84, Cat C: 2.89, Cat D: 3.78. Order 8260.3, chapter 2, New Circling Criteria Applied. Airport elevation changed from 914 to 913.

Last Updated By: Kweku Donkor

Last Updated At: 2021-06-29 14:22:37.348067      1/2828

Status: Verified

!FDC X/XXXX DKB IAP DE KALB TAYLOR MUNI, DE KALB, IL. RNAV (GPS) RWY 2, ORIG-A... APT ELEV 913. CIRCLING CAT A HAA 447, CAT B MDA 1500/HAA 587, CAT C MDA 1600/HAA 687, CAT D MDA 1740/HAA 827. VISIBILITY CAT C 2, CAT D 2 3/4. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 900-2 3/4, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 2, ORIG-B. 2106291422-PERM

*Digitally signed by*  
**DAVID TEFFETELLER**  
Jul 01, 2021

