

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
JEDGI	ONE	JEDGI1.JEDGI	NONE		

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

DP ROUTE DESCRIPTION:

RWY 1: CLIMB ON HEADING 013.65 TO 2800 THEN CLIMBING RIGHT TURN HEADING 160.00 TO INTERCEPT PRB VORTAC R-040 TO PRB VORTAC, THEN ON R-178.50 TO JEDGI/PRB 12.50 DME, THENCE...

RWY 13: CLIMBING RIGHT TURN ON HEADING 210.00 TO INTERCEPT PRB VORTAC R-178.50 TO JEDGI/PRB 12.50 DME, THENCE...

RWY 19: CLIMBING LEFT TURN ON HEADING 150.00 TO INTERCEPT PRB VORTAC R-178.50 TO JEDGI/PRB 12.50 DME, THENCE...

RWY 31: CLIMB ON HEADING 308.65 TO 1800 THEN CLIMBING RIGHT TURN HEADING 110.00 TO INTERCEPT PRB VORTAC R-360 TO PRB VORTAC, THEN ON R-178.50 TO JEDGI/PRB 12.50 DME THENCE...

...MAINTAIN ATC ASSIGNED ALTITUDE; EXPECT CLEARANCE TO FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	-------------------------------------	----------------------------	--------------------------	---------------	-----------------	------------	-------------	------------------------------------

PROCEDURAL DATA NOTES:

NOTE: DME REQUIRED

TAKEOFF MINIMUMS:

RWY 19: STANDARD

RWY 1: STANDARD WITH MINIMUM CLIMB OF 230 FT PER NM TO 2200

RWY 13: STANDARD WITH MINIMUM CLIMB OF 220 FT PER NM TO 1700

RWY 31: STANDARD WITH MINIMUM CLIMB OF 235 FT PER NM TO 2200

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

RWY 1: 1839 FT MSL AAO 354523.33N/1203233.86W

RWY 13: 1419 FT MSL AAO 353704.87N/1203438.79W

RWY 31: 1799 FT MSL AAO 354608.24N/203907.51W

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

CHART: TOP ALTITUDE: ASSIGNED BY ATC

REFERENCE MAG VAR: KPRB 15E EPOCH YR: 1980

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>
PASO ROBLES MUNI	KPRB	PASO ROBLES	CA



Page 2 of 2