

[Print](#)

Project Name: MKY - NEW CIRCLING AREAS

Project Reason: ORDER 8260.3, CHAPTER 2, NEW CIRCLING CRITERIA APPLIED CONTROLLING OBSTACLES: CAT A/B BUILDING (12-003426) 255940.34N/0814146.31W 258 (5D) + AC 50 + ROC 300 = MDA 620 CAT C TOWER (12-002721) 260151.21N/0813827.15W 346 (1A) + ROC 300 = MDA 660 CAT D TOWER (12-000212) 260311.32N/0814210.40W 534 (1A) + ROC 300 = MDA 840 RADII: CAT A 1.30, CAT B 1.81, CAT C 2.83, 3.70.

Last Updated By: Chris McCarthy

Last Updated At: 2021-04-21 15:03:16.907486

Status: Verified **1/5291**

!FDC X/XXXX MKY IAP MARCO ISLAND EXEC, MARCO ISLAND, FL. RNAV (GPS) RWY 17, ORIG-A... CIRCLING CAT C MDA 660/HAA 655, CAT D MDA 840/HAA 835, CAT D VIS 2 3/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE NAPLES ALTIMETER SETTING AND INCREASE LPV DA TO 326 FEET; INCREASE LNAV/VNAV DA TO 484 FEET, INCREASE ALL MDAS 40 FEET AND LNAV VISIBILITY CAT C TO 1 1/4 SM AND CIRCLING VISIBILITY CAT C TO 2 SM. ALTERNATE MINIMUMS STANDARD EXCEPT CAT D 900-2 3/4, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 17, ORIG-B. 2104211503-PERM

*Digitally signed by*  
**JASON KRETSCHMER**  
Apr 25, 2021

