

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> 26R	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 33	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>CITY</u> EDNA	<u>STATE</u> TX
<u>AIRPORT ELEVATION</u> 62	<u>TDZE</u> 61	<u>SUPERSEDED</u>	<u>ORIGINAL/AMENDMENT</u> NONE	<u>DATED</u>
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u>	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>MAG VAR</u> 3E
				<u>EPOCH YEAR</u> 2020
				<u>CANCEL/SUSPEND</u>

TAA

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>ALTITUDE</u>
1. 237/30 CW 057/30	NOPT	237/15 CW 057/15		2600
2. 237/15 CW 057/15		MERRY	IF/IAF	2200
3. 057/30 CW 237/30		MERRY	IF/IAF	2200

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
MERRY	IF/IAF	PLOTS		TF	FB	1.00	326.69	6.10	1600
PLOTS	FAF	RW33	MAP	TF	FO	0.30	326.66	4.71	
RW33	MAP	315 MSL		CA			326.66		
315 MSL		ZEDNA		DF	FO	1.00			2200

MISSED APPROACH

MAP:

LPV: DA
LNAV/VNAV: DA
LNAV: RW33

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 2200 DIRECT ZEDNA AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



PROFILE:

1.	PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)									
2.	HOLD SE MERRY, RT, 326.69 INBOUND, 2200 FT. IN LIEU OF PT (IAF), MAX 6000.														
3.	FAC:	326.66	FAF:	PLOTS	DIST FAF TO MAP:	4.71	DIST FAF TO THLD:	4.71							
4.	MIN ALT:	MERRY 2200, PLOTS 1600													
5.	DIST TO THLD FROM OM:		MM:		IM:		150 HAT:		254 HAT:	0.67	GS ANT:				
6.	MIN GP INCPT:	1600	GP ALT AT PFAF:	PLOTS 1600					OM:		MM:			IM:	
7.	GP ANGLE:	3.00	34:1:	IS CLEAR	20:1:	IS CLEAR	TCH:	40.0							
8.	MSA FROM:														

PBN REQUIREMENTS NOTE:

RNP APCH - GPS.

NOTES:

CHART NOTE: BARO-VNAV NA.
CHART NOTE: USE VCT ALTIMETER SETTING, WHEN NOT RECEIVED, USE PKV ALTIMETER SETTING.

ADDITIONAL FLIGHT DATA:

CHART VCT ASOS-3.
HOLD NW, RT, 146.58 INBOUND.
FAS OBST: 253 AAO 285657N/0963251W.
WAAS CHANNEL # 97348
REFERENCE PATH ID: W33A
LTP HAE: -8.9 M

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☒

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LPV DA	315	3/4	254	315	3/4	254		NA			NA				
LNAV/VNAV DA	365	7/8	304	365	7/8	304		NA			NA				
LNAV MDA	560	1	499	560	1	499		NA			NA				

CHANGES - REASONS

9/16/24: THIS IS A CORRECTED COPY OF THE FORM APPROVED ON 8/2/24.
1 REMOVED "PLOTS TO RW33: 3.00/40" FROM ADDITIONAL FLIGHT DATA.



COORDINATED WITH:

A4A

☐

ALPA

☒

AOPA

☒

APA

☒

HAI

☐

NBAA

☒

OTHER: ZHU ARTCC, AMGR

FLIGHT CHECKED BY
BRIAN DAVID HARRELSON

Digitally signed by
DAVID DANNER
Sep 17, 2024

OFFICE
FIOG

DATE
08/23/2024

DEVELOPED BY
JOHN BORDY (LEO PALMER)

Digitally signed by
LEO PALMER
Sep 16, 2024

OFFICE
AJV-A33

DATE
02/28/2024

APPROVED BY
JOHN BORDY

Digitally signed by
DAVID DANNER
Sep 17, 2024

OFFICE
AJV-A33

DATE

TITLE
MANAGER

FAS DATA BLOCK INFORMATION

DATA FIELD	DATA
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	26R
RUNWAY	RW33
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W33A
LTP/FTP LATITUDE	285949.1055N
LTP/FTP LONGITUDE	0963445.4060W
LTP/FTP ELLIPSOIDAL HEIGHT	-00089
FPAP LATITUDE	290106.1790N
FPAP LONGITUDE	0963536.7760W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1720
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
CRC REMAINDER	146DDA33

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00184
FPAP ORTHOMETRIC HEIGHT	+00184



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD INSTRUMENT APPROACH PROCEDURE DATA RECORD**

<u>AIRPORT ID</u>	<u>PROCEDURE NAME</u>	<u>AMDT NO.</u>	<u>CITY</u>	<u>STATE</u>	<u>AIRPORT ELEVATION</u>	<u>FACILITY</u>
26R	RNAV (GPS) RWY 33	ORIG	EDNA	TX	62	RNAV

PART A: OBSTRUCTION DATA SEGMENTS

STRAIGHT-IN AREA

FROM 237/30 CW 057/30 **TO** 237/15 CW 057/15

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>		<u>HAT</u>				<u>HMAS</u>		
<u>OBSTRUCTION</u>	<u>COORDINATES</u>	<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
TOWER (48-014729)	284801.00N/0960732.90W	1541	500	50	5D	1000					2600
TERRAIN	284027.00N/0963245.00W	118 (100)								AS1500	1600

COMPUTATIONS

ALT KIAS KTAS HAA VKTW TR BA DTA COURSE CHANGE DVEB VEB OCS RF CENTER FIX/DISTANCE

SEGMENT REMARKS:

STRAIGHT-IN AREA

FROM 237/15 CW 057/15 **TO** MERRY

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>			<u>HAT</u>			<u>HMAS</u>		
<u>OBSTRUCTION</u>	<u>COORDINATES</u>	<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
TOWER (48-007967)	285323.19N/0962141.87W	1049	250	50	4D	1000				AT151	2200
TERRAIN	284027.00N/0963245.00W	118 (100)								AS1500	1600

COMPUTATIONS

ALT KIAS KTAS HAA VKTW TR BA DTA COURSE CHANGE DVEB VEB OCS RF CENTER FIX/DISTANCE

SEGMENT REMARKS:

QUALITY
25
CHECKED

STRAIGHT-IN AREA

FROM

057/30 CW 237/30

TO

MERRY

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>		<u>HAT</u>		<u>HMAS</u>				
<u>OBSTRUCTION</u>	<u>COORDINATES</u>	<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
TOWER (48-012937)	284224.80N/0965006.80W	1053	500	50	5D	1000				AT147	2200
TERRAIN	290339.00N/0965903.00W	190 (200)								AS1500	1700

COMPUTATIONS

ALT

KIAS

KTAS

HAA

VKTW

TR

BA

DTA

COURSE CHANGE

DVEB

VEB OCS

RF CENTER FIX/DISTANCE

SEGMENT REMARKS:

INTERMEDIATE

FROM

MERRY (IF/IAF)

TO

PLOTS

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>		<u>HAT</u>		<u>HMAS</u>				
1.00	6.10										
<u>OBSTRUCTION</u>	<u>COORDINATES</u>	<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
TOWER (48-009780)	285140.00N/0962713.00W	354	20	3	1A	500					900
TERRAIN	285330.00N/0963254.00W	52 (100)								AS1500	1600

COMPUTATIONS

ALT

KIAS

KTAS

HAA

VKTW

TR

BA

DTA

COURSE CHANGE

DVEB

VEB OCS

RF CENTER FIX/DISTANCE

SEGMENT REMARKS:



FINAL: LPV

FROM

PLOTS

TO

RW33

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>				<u>HAT</u>	<u>HMAS</u>			
0.30	4.71		DA				254				
<u>OBSTRUCTION</u>	<u>COORDINATES</u>	<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
							ASC			RA54	315

COMPUTATIONS

ALT

KIAS

KTAS

HAA

VKTW

TR

BA

DTA

COURSE CHANGE

DVEB

VEB OCS

RF CENTER FIX/DISTANCE

SEGMENT REMARKS:

FINAL: LNAV/VNAV

FROM

PLOTS

TO

RW33

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>				<u>HAT</u>	<u>HMAS</u>			
0.30	4.71		DA				304				
<u>OBSTRUCTION</u>	<u>COORDINATES</u>	<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
							ASC			RA54	365

COMPUTATIONS

ALT

KIAS

KTAS

HAA

VKTW

TR

BA

DTA

COURSE CHANGE

DVEB

VEB OCS

RF CENTER FIX/DISTANCE

SEGMENT REMARKS:

FINAL: LNAV

FROM

PLOTS

TO

RW33

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>				<u>HAT</u>	<u>HMAS</u>			
0.30	4.71		RW33				499				
<u>OBSTRUCTION</u>	<u>COORDINATES</u>	<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
AAO	285657.00N/0963251.00W	253	215	8	4B	250				RA54	560

COMPUTATIONS

ALT

KIAS

KTAS

HAA

VKTW

TR

BA

DTA

COURSE CHANGE

DVEB

VEB OCS

RF CENTER FIX/DISTANCE

SEGMENT REMARKS:

HOLD-IN-LIEU OF PT

FROM

MERRY

TO

P-5

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u> P-5	<u>MAP</u>				<u>HAT</u>	<u>HMAS</u>			
<u>OBSTRUCTION</u>	<u>COORDINATES</u>	<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
TOWER (48-000983)	285439.00N/0962744.00W	370	500	50	5D	1000				AT830	2200
TERRAIN	285521.00N/0962915.00W	55 (100)								AS1500	1600

COMPUTATIONS

ALT

KIAS

KTAS

HAA

VKTW

TR

BA

DTA

COURSE CHANGE

DVEB

VEB OCS

RF CENTER FIX/DISTANCE

SEGMENT REMARKS:

MISSED APPROACH: LPV

FROM

DA

TO

ZEDNA

<u>RNP</u> 0.30-1.00	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>				<u>HAT</u>	<u>HMAS</u> 96			
<u>OBSTRUCTION</u>	<u>COORDINATES</u>	<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
							ASC				2200
TOWER (48-020583)	290910.65N/0963902.25W	439	250	50	4D	1000					1500
TERRAIN	290945.00N/0964106.00W	118 (100)								AS1500	1600

COMPUTATIONS

ALT

KIAS

KTAS

HAA

VKTW

TR

BA

DTA

COURSE CHANGE

DVEB

VEB OCS

RF CENTER FIX/DISTANCE

SEGMENT REMARKS:



MISSED APPROACH: LNAV/VNAV

FROM

DA

TO

ZEDNA

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>				<u>HAT</u>	<u>HMAS</u>			
0.30-1.00										169	
<u>OBSTRUCTION</u>	<u>COORDINATES</u>	<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
							ASC				2200
TOWER (48-020583)	290910.65N/0963902.25W	439	250	50	4D	1000					1500
TERRAIN	290945.00N/0964106.00W	118 (100)								AS1500	1600

COMPUTATIONS

ALT

KIAS

KTAS

HAA

VKTW

TR

BA

DTA

COURSE CHANGE

DVEB

VEB OCS

RF CENTER FIX/DISTANCE

SEGMENT REMARKS:

MISSED APPROACH: LNAV

FROM

RW33

TO

ZEDNA

<u>RNP</u>	<u>DISTANCE</u>	<u>PAT</u>	<u>MAP</u>				<u>HAT</u>	<u>HMAS</u>			
0.30-1.00											406
<u>OBSTRUCTION</u>	<u>COORDINATES</u>	<u>ELEV MSL</u>	<u>HORZ</u>	<u>VERT</u>	<u>AC</u>	<u>ROC</u>	<u>OCS</u>	<u>CG</u>	<u>CGTA</u>	<u>ADJUSTMENTS</u>	<u>MIN ALT</u>
							ASC				2200
TOWER (48-020583)	290910.65N/0963902.25W	439	250	50	4D	1000					1500
TERRAIN	290945.00N/0964106.00W	118 (100)								AS1500	1600

COMPUTATIONS

ALT

KIAS

KTAS

HAA

VKTW

TR

BA

DTA

COURSE CHANGE

DVEB

VEB OCS

RF CENTER FIX/DISTANCE

SEGMENT REMARKS:

MSA/ESA

CENTER

RADIUS

REMARKS:

NOTES/EXPLANATIONS FROM PROCEDURE SEGMENTS:



PART B: SUPPLEMENTAL DATA

COMMUNICATIONS WITH

MONTGOMERY COUNTY FSS, ZHU ARTCC

<u>WX SERVICE</u>	<u>LOCATION</u>	<u>HRS OPERATION</u>	<u>ALTIMETER SOURCE</u>	<u>DISTANCE</u>	<u>SERVICE-A</u>	<u>ADJUSTMENTS</u>
ASOS	VCT	24	VCT	19.82	Y	54
<u>BACK-UP WX SERVICE</u>	<u>LOCATION</u>	<u>HRS OPERATION</u>	<u>ALTIMETER SOURCE</u>	<u>DISTANCE</u>	<u>SERVICE-A</u>	<u>ADJUSTMENTS</u>
AWOS-3	PKV	24	PKV	21.48	Y	54

WX REMARKS:

RASS PRESSURE PATTERNS THE SAME
K26R 62, KVCT 115
RA= 53.2

RASS PRESSURE PATTERNS THE SAME
K26R 62,PKV 32
RA= 53.6

<u>PRIMARY NAVAID</u>	<u>MONITOR POINT</u>	<u>HRS OPERATION</u>	<u>CAT</u>
<u>APPROACH AND RUNWAY LIGHTING SYSTEM</u>		<u>RUNWAY MARKINGS</u>	<u>RUNWAY VISUAL RANGE</u>
RW15 - MIRL (PCL)		NPI-G	
RW33 - MIRL (PCL)		NPI-G	

<u>GLIDESLOPE ANGLE</u>	<u>ELEV RWY THRESHOLD</u>	<u>TCH</u>	<u>ELEV GS ANTENNA</u>	<u>DISTANCE FROM RWY</u>	<u>VGSI ANGLE</u>	<u>TCH</u>
3.00	60.5	40.0				

FINAL APPROACH COURSE AIMING

RUNWAY THRESHOLD	<div>X</div>	FT FROM THRESHOLD	DISPLACED THRESHOLD DISTANCE
ON CENTERLINE	<div>X</div>	FT FROM CENTERLINE	

CRITICAL TEMPERATURES

<u>CRITICAL LOW</u>	<u>CRITICAL HIGH</u>	<u>ACT</u>	<u>APT ISA</u>
-15C	+54C	+15C	+14.88C

CRITICAL TEMPERATURE REMARKS:

AVERAGE COLD TEMPERATURE DERIVED FROM STANDARD -30C ISA DEVIATION.
CRITICAL LOW TEMPERATURE BASED ON ACT.
DESCENT RATE (FPM): STANDARD TEMP 709 HIGH TEMP 1124.

"VISUAL PORTION OF FINAL" PENETRATIONS



HELICOPTER 'VISUAL PORTION OF FINAL' PENETRATIONS

and/or

5280-FT "PROCEED VFR" SEGMENT LEVEL SURFACE AREA PENETRATIONS

PENETRATIONS REMARKS:

PART C: GENERAL REMARKS:

PRECIPITOUS TERRAIN EVALUATION COMPLETED.
VDP NOT ESTABLISHED - PRIMARY ALTIMETER IS REMOTE.
VEGETATION HEIGHT: 75 FT
NO VGSI DATA.

NO CIRCLING MINIMUMS PER FPT CHECKLIST.
PART D: AIRSPACE

DOCKET #

ALL DISTANCES TO 1/100NM; ELEVATION TO NEAREST 100 FEET; COORDINATES TO 1/100 SECOND; DEG TO 1/100 DEGREE

DISTANCE FROM	THLD	TO 1000FT POINT	3.14
WIDTH OF	FINAL	SEGMENT AT 1000FT POINT	1.20
TRUE COURSE OF	FINAL	SEGMENT CONTAINING 1000FT POINT	329.66
HIGH TERRAIN IN	FINAL	SEGMENT CONTAINING 1000FT POINT	100
DISTANCE FROM	THLD	TO 1500FT POINT	4.71
WIDTH OF	FINAL	SEGMENT AT 1500FT POINT	2.13
TRUE COURSE OF	FINAL	SEGMENT CONTAINING 1500FT POINT	329.66
HIGH TERRAIN IN	FINAL	SEGMENT CONTAINING 1500FT POINT	100

THRESHOLD COORDINATES (IF STR-IN)	285949.11N/0963445.41W
ARP COORDINATES	290003.60N/0963455.06W
RUNWAY APCH END AND DIST FURTHEST FROM ARP	RUNWAY 33 DISTANCE 0.28 NM
FAF COORDINATES	285544.68N/0963202.66W
FIX NAME COORDINATES	IF/IAF MERRY 285027.95N/0962832.13W

REMARKS

NO ADDITIONAL AIRSPACE REQUIRED
IF/IAF MERRY 285027.95N 0962832.13W 30 NM RADIUS

PART E: PREPARED BY

NAME	OFFICE	DATE	TITLE
JOHN BORDY (LEO PALMER)	AJV-A33	02/28/2024	AERONAUTICAL INFORMATION SPECIALIST

