

[Print](#)

Project Name: IWD - RNAV GPS RWY 27 NEW CIRCLING AREA

Project Reason: CIRCLING CONTROLLING OBSTACLES: CAT A: 1622 TREE 463021.24N/0900739.68W (2C) (1622 MSL + 300 ROC = 1922 (1940 MDA), CAT B: 1759 TREE 462954.95N/0900612.65W (2C) (1759 MSL + 300 ROC = 2059 (2060 MDA), CAT C: 1899 TREE 462903.18N/0900646.89W (2C) (1899 MSL + 300 ROC = 2199 (2200 MDA), CAT D: 1920 AAO 462914.18N/0900334.66W (2C) (1920 MSL + 300 ROC = 2220 MDA). RADII: 1.31, 1.85, 2.91, 3.80. UPDATED BU ALSTG, EQUIPMENT AND BARO-VNAV NOTES AND ALTERNATE MINIMUMS. ORDER 8260.3, CHAPTER 2, NEW CIRCLING CRITERIA APPLIED.

Last Updated By: Steven Dougherty

Last Updated At: 2021-04-27 23:29:45.051951

Status: Verified **1/6486**

!FDC X/XXXX IWD IAP GOGEBIC-IRON COUNTY, IRONWOOD, MI. RNAV (GPS) RWY 27, ORIG... CIRCLING CAT C MDA 2200/HAA 970, VISIBILITY CAT A 1 1/4, CAT C 3. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ASHLAND ALTIMETER SETTING: INCREASE LPV DA TO 1562 FEET; INCREASE LNAV/VNAV DA TO 2298 FEET AND CAT C VISIBILITY 1/4 SM; INCREASE ALL MDA 140 FEET AND LNAV CAT C/D VISIBILITY 1/2 SM AND CIRCLING CAT B VISIBILITY 1/4 SM. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 46C. ALTERNATE MINIMUMS: CAT A, B 900-2, CAT C, D 1000-3, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 27, ORIG-A. 2104272329-PERM

Digitally signed by
JASON KRETSCHMER
May 09, 2021

