

[Print](#)

Project Name: DIK - Circling Icon

Project Reason: CHART CIRCLING ICON. CIRCLING UPDATED TO MATCH OTHER PROCEDURE WITH NEW CIRCLING ICON/RADII (ILS OR LOC RWY 32). CIRCLING OBSTRUCTIONS: CAT A: 2719 RIG (38-000534), 464910.00N/1024851.00W (5D), CAT B: 2771 TREE, 464745.00N/1024500.00W (4D), CAT C: 2807 TOWER (38-023111), 464443.27N/1024702.53W (1A), CAT D: 2894 AAO, 464536.00N/1025254.00W (4D). RADII: CAT A: 1.34, CAT B: 1.90, CAT C: 3.00, CAT D: 3.92.

Last Updated By: DALE SICKELS

*Digitally signed by*

**DAVID DANNER**

Last Updated At: 2019-12-11 14:33:34.720148

Feb 28, 2020

Status: Verified

!FDC 0/1185 DIK IAP DICKINSON - THEODORE ROOSEVELT RGNL, DICKINSON, ND. RNAV (GPS) RWY 32, AMDT 2A... CHART CIRCLING ICON. CIRCLING CAT B MDA 3100/HAA 508, CAT C MDA 3120/HAA 528, CAT D MDA 3220/HAA 628. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BOWMAN ALTIMETER SETTING AND INCREASE ALL DA 266 FEET, ALL MDA 280 FEET, INCREASE LPV ALL CATS VISIBILITY 1/2 SM, LNAV/VNAV CATS A/B/C VISIBILITY 1 SM, CAT D VISIBILITY 3/4 SM, LNAV CATS C/D VISIBILITY 3/4 SM, CIRCLING CAT C VISIBILITY 3/4 SM, CAT D VISIBILITY 1 SM. DELETE CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BOWMAN ALTIMETER SETTING AND INCREASE ALL DA 266 FEET, ALL MDA 280 FEET, INCREASE LPV ALL CATS VISIBILITY 1/2 SM, LNAV/VNAV CATS A/B/C VISIBILITY 1 SM, CAT D VISIBILITY 3/4 SM, LNAV CATS C/D VISIBILITY 3/4 SM, CIRCLING CAT B VISIBILITY 1/4 SM, CATS C/D VISIBILITY 3/4 SM. THIS IS RNAV (GPS) RWY 32, AMDT 2B. 1912111433-PERM

