

[Print](#)

Project Name: OPF CIRC ICON

Project Reason: CONTROLLING OBSTACLE: CAT C: 12-117777 314 ANT 255737.33N/0801614.34W (1B). 314 (OBS) + 300 (ROC) = 614/620 MDA/612 HAA. CAT D: 12-003042 376 BLDG 255732.11N/0801421.50 (5D). 376 (OBS) + 300 (ROC) + 50 (AC) = 726/740 MDA/732 HAA.. VIS CHECK: C: 1 3/4 D: 2 1/4. RADII: A: 1.30 B: 1.81 C: 2.83 D: 3.70 BACKUP ALTIMETER NOTE FOR CIRC UPDATED, STRAIGHT-IN NOT VERIFIED. ORDER 8260.3, CHAPTER 2, NEW CIRCLING CRITERIA APPLIED

Last Updated By: david Teffeteller

Last Updated At: 2021-04-28 13:34:06.442318

Status: Draft

1/9984

!FDC X/XXXX OPF IAP MIAMI-OPA LOCKA EXEC, MIAMI, FL. RNAV (GPS) RWY 27R, ORIG-C... CIRCLING CAT C MDA 620/HAA 612, CAT D MDA 740/HAA 732; VIS CAT C 1 3/4, CAT D 2 1/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MIAMI INTL ALTIMETER SETTING AND INCREASE ALL DA/MDA 20 FEET AND CIRCLING CAT D VISIBILITY 1/4 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4, NA WHEN LOCAL WEATHER NOT AVAILABLE.. THIS IS RNAV (GPS) RWY 27R, ORIG-D. 2104281334-PERM

QUALITY

45

CHECKED

Digitally signed by  
**DAVID TEFFETELLER**  
May 04, 2021