

[Print](#)

Project Name: KWVL RNAV GPS RWY 5 - NEW CIRCLING RADII

Project Reason: New circling areas established. Controlling obstacles: Cat A/B: TREE 443231.58N/0694154.17W, 549, 2C (maintained previous minimums). 549 + 300 (ROC) = 860 MDA. Cat C: TOWER (23-000383) 443315.00N/0694421.00W, 734, 5D (new, maintained previous minimums). 734 + 300 (ROC) + 50 (AC) = 1100 MDA. Cat D: TOWER (23-000522) 443316.08N/0694427.01W, 759, 4D (new). 759 + 300 (ROC) + 50 = 1120 MDA. Radii: Cat A: 1.30, Cat B: 1.82, Cat C: 2.85, Cat D: 3.73. Order 8260.3, chapter 2, New Circling Criteria Applied. BACKUP ALTIMETER NOTE FOR CIRCLING VERIFIED; STRAIGHT-IN MINIMUMS NOT VERIFIED.

Last Updated By: Kweku Donkor

Last Updated At: 2021-05-24 16:12:44.9988

Status: Verified

1/2568

!FDC X/XXXX WV L IAP WATERVILLE ROBERT LAFLEUR, WATERVILLE, ME. RNAV (GPS) RWY 5, AMDT 1C... CIRCLING CAT C MDA 1100/HAA 767, CAT D MDA 1120/HAA 787; VIS CAT C 2 1/4, CAT D 2 1/2. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AUGUSTA ALTIMETER SETTING; INCREASE LPV DA TO 544 FEET, LNAV/VNAV DA TO 623 FEET AND ALL VISIBILITIES 7/8 SM; INCREASE ALL MDAS 40 FEET AND CIRCLING CAT C VISIBILITY 1/4 SM. ALTERNATE MINIMUMS: STANDARD - CAT C 800-2 1/4, CAT D 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 5, AMDT 1D. 2105241612-PERM

Digitally signed by
DAVID TEFFETELLER
Jun 14, 2021

