

[Print](#)

Project Name: KOCF NEW CIRCLING RADII APPLIED

Project Reason: New circling areas established. Controlling obstacles: Cat A: Tower (12-142864) 291130.68N/0821345.53W 237 (4D) + AC 50 + ROC 300 = MDA 600. Cat B: Tower (12-020051) 290923.72N/0821455.51W 276 (1A) + ROC 300 = MDA 580 (600 for lower Cat). Cat C: Tower (12-003224) 291131.00N/0821016.00W 399 (5D) + AC 50 + ROC 300 = MDA 760. Cat D: Tower (12-001086) 291040.00N/0820933.00W 564 (4D) + AC 50 + ROC 300 = MDA 920. Radii: Cat A: 1.30 Cat B: 1.81 Cat C: 2.84 Cat D: 3.71. Order 8260.3, chapter 2, New Circling Criteria Applied.

Last Updated By: James Lafferty

Last Updated At: 2021-03-23 10:54:48.25918

1/8485

Status: Draft

!FDC X/XXXX OCF IAP OCALA INTL-JIM TAYLOR FLD, OCALA, FL. VOR RWY 36, AMDT 18... CIRCLING CAT A/B HAA 550, CAT C MDA 760/HAA 670, CAT D MDA 920/HAA 830, VIS CAT C 1 3/4, CAT D 2 3/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GAINESVILLE ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET; INCREASE S-36 CATS C/D AND CIRCLING CAT D VISIBILITIES 1/4 SM AND CIRCLING CAT C VISIBILITY 1/2 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 900-2 3/4 - NA WHEN LOCAL WEATHER NOT AVAILABLE. DELETE APT ELEV 89. CHART APT ELEV 90. THIS IS VOR RWY 36, AMDT 18A. 2103231054-PERM

QUALITY
45
CHECKED

Digitally signed by
DAVID TEFFETELLER
Mar 23, 2021