

[Print](#)

Project Name: GYY RNAV (GPS) RWY 20 NEW CIRCLING RADII APPLIED/STRAIGHT-IN

Project Reason: ORDER 8260.3, CHAPTER 2, NEW CIRCLING CRITERIA APPLIED - CATEGORY RADII: CAT A: 1.30, CAT B: 1.83, CAT C: 2.87 AND CAT D: 3.75. CONTROLLING OBSTACLE CAT A 791 MSL/199 AGL TANK (18-041700) 413757.68N/0872408.22W (1B), OBS 791 + ROC 300 + XP 49 = 1140. CONTROLLING OBSTACLE CAT B 864 MSL/270 AGL STACK (18-000573) 413725.00N /0872208.00W (1A), OBS 864 + ROC 300 = 1164 (1180). CONTROLLING OBSTACLE CAT C 1093 MSL/498 AGL TOWER (18-041303) 413358.15N /0872506.13W (1B), OBS 1093 + ROC 300 = 1393 (1400). CONTROLLING OBSTACLE CAT D 1103 MSL/507 AGL TOWER (18-001767) 413314.75N /0872225.23W (1A), OBS 1103 + ROC 300 = 1403 (1420). UPDATE AND/OR ADD NOTES, VISIBILITIES, ALTERNATE MINIMUMS WHERE REQUIRED.

Last Updated By: Andre Marsh

Last Updated At: 2022-01-24 17:05:11.83987

Status: Verified **2/7087**



!FDC X/XXXX GYY IAP GARY/CHICAGO INTL, GARY, IN. RNAV (GPS) RWY 20, ORIG... APT ELEV 597 FEET. CIRCLING CAT A HAA 543, CAT B MDA 1180/HAA 583, CAT C MDA 1400/HAA 803, CAT D MDA/HAA 1420/823. VISIBILITY CAT C 2 1/4 AND CAT D 2 3/4. ALTERNATE MINIMUMS STANDARD EXCEPT CAT C 900-2 1/4 AND CAT D 900-2 3/4. THIS IS RNAV (GPS) RWY 20, ORIG-A. 2201241643-PERM

Digitally signed by
JASON KRETSCHMER
Jan 24, 2022