

[Print](#)

Project Name: KAQP NEW CIRCLING RADII APPLIED

Project Reason: Evaluation of Expanded Circling Criteria. Updated alternate mins and secondary altimeter notes as necessary. Only circling visibility verified. Controlling obstacles: CAT A/B: 1149 Tree 451247.00N/0955823.00 (2C). 1149+300 (ROC) = 1460 MDA/HAA 439. CAT C: 1532 Tower (27-000444) 451049.00N/0955948.00W (5D). 1532 + 50 (AC) + 300 (ROC) = 1900 MDA/HAA 879. Radii: CAT A: 1.30, CAT B 1.84, CAT C 2.90. Order 8260.3, chapter 2, New Circling Criteria Applied.

Last Updated By: James Lafferty

Last Updated At: 2021-06-16 11:29:10.143055

Status: Draft

1/5573

!FDC X/XXXX AQP IAP APPLETON MUNI, APPLETON, MN. RNAV (GPS) RWY 13, ORIG... CIRCLING CAT C MDA 1900/HAA 879, VIS CAT C 2 1/2. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BENSON ALTIMETER SETTING AND INCREASE ALL MDAS 40 FEET, AND INCREASE CIRCLING CAT C VISIBILITY 1/4 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT C 900-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 13, ORIG-A. 2106161129-PERM

Digitally signed by  
**DAVID TEFFETELLER**  
Jun 17, 2021

