

[Print](#)

Project Name: KARG NEW CIRCLING RADII APPLIED

Project Reason: Expanded circling area applied. Updated alternate minimums and secondary altimeter notes as required. Only circling visibility verified. Controlling obstacles: CAT A/B: 395 TANK (05-000866) 360722.00N/0905610.00W (4D). 395+300(ROC)+50(AC)=760 MDA/HAA 481. CAT C: 446 TOWER (05-006375) 360410.00N/0905720.00W (4D). 446+300(ROC)+50(AC)=800 MDA/HAA 521. CAT D: 688 TOWER (05-001341) 360330.00N/0905636.00W (1A). 688+300(ROC)=1000 MDA/HAA 721. Radii: CAT A: 1.30, CAT B: 1.81, CAT C: 2.85, CAT D 3.72. Order 8260.3, chapter 2, New Circling Criteria Applied.

Last Updated By: James Lafferty

Last Updated At: 2021-03-29 10:57:13.266378

1/2789

Status: Draft

!FDC X/XXXX ARG IAP WALNUT RIDGE RGNL, WALNUT RIDGE, AR. RNAV (GPS) RWY 4, ORIG-A... CIRCLING CATS A/B/C MDA 840/HAA 561, CIRCLING CAT D MDA 1000/HAA 721, VIS CAT D 2 1/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JONESBORO ALTIMETER SETTING AND INCREASE LPV AND LNAV/VNAV DA TO 583 FEET, AND ALL MDAS 60 FEET; INCREASE CIRCLING CATS C/D VISIBILITY 1/4 SM. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4 - NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 4, ORIG-B. 2103291057-PERM

Digitally signed by
DAVID TEFFETELLER
Apr 01, 2021

