

[Print](#)

Project Name: MML NEW CIR RADII

Project Reason: ORDER 8260.3, CHAPTER 2, NEW CIRCLING CRITERIA APPLIED: CATEGORY RADII: CAT A: 1.31, CAT B: 1.85, CAT C: 2.91 AND CAT D: 3.80. CONTROLLING OBSTACLE CAT A/B 1336 MSL TOWER (27-023808) 442701.80N/0954741.34W (1A), OBS 1336 + ROC 300 = 1636 (1640). CONTROLLING OBSTACLE CAT C 1515.0 MSL TOWER (27-050700) 442656.95N/0954543.51W (1B), OBS 1515 + ROC 300 = 1815 (1820). CONTROLLING OBSTACLE CAT D 1540.0 MSL AAO 442418.72N /0955323.19W (2C), OBS 1540 + ROC 300 = 1840. UPDATE NOTES, VISIBILITIES AND ALTERNATE MINIMUMS WHERE APPLICABLE.

Last Updated By: Andre Marsh

Last Updated At: 2021-04-20 17:53:09.325193

Status: Verified **1/9868**

IFDC X/XXXX MML IAP SOUTHWEST MINNESOTA RGNL MARSHALL/RYAN FLD, MARSHALL, MN. ILS OR LOC RWY 12, AMDT 2A... TDZE 1183. APT ELEV 1183. S-ILS DA 1383. S-LOC HAT 377 ALL CATS, CAT C/D 5/8. CIRCLING CAT A/B HAA 457, CAT C MDA 1820/HAA 637, CAT D MDA 1840/HAA 657, CAT C 1 3/4. DELETE NOTE: ADF REQUIRED. DELETE PLANVIEW NOTE: ADF OR DME REQUIRED. EQUIPMENT REQUIREMENTS NOTE: ADF OR DME REQUIRED. DELETE PROFILE NOTE: VGSI AND ILS GLIDEPATH NOT COINCIDENT (VGSI ANGLE 3.00/TCH 50). CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TRACY MUNI ALTIMETER SETTING AND INCREASE ILS DA TO 1441 FEET AND ALL MDA 60 FEET, S-LOC CAT C/D VISIBILITY 1/8 SM AND CIRCLING VISIBILITY CAT C/D 1/4 SM. DELETE NOTE: FOR INOPERATIVE MALSR WHEN USING TRACY MUNI ALTIMETER SETTING, INCREASE S-ILS 12 VISIBILITY TO 1 MILE ALL CATS. CHART NOTE, INOPERATIVE TABLE DOES NOT APPLY. FOR INOPERATIVE ALS INCREASE S-LOC 12 ALL CATS VISIBILITY TO 1 SM. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY WHEN USING TRACY MUNI ALTIMETER SETTING. FOR INOPERATIVE ALS WHEN USING TRACY MUNI ALTIMETER SETTING, INCREASE S-LOC 12 CAT A/B VISIBILITY TO 1 SM.. THIS IS ILS OR LOC RWY 12, AMDT 2B. 2104201753-PERM

Digitally signed by
JASON KRETSCHMER
May 04, 2021

