

[Print](#)

Project Name: RKW - NEW CIRCLING AREA

Project Reason: NEW CIRCLING AREA. UPDATED BACKUP ALTIMETER NOTES. CONTROLLING OBSTACLES: CAT A: 1799 TREE 355356.73N/0844210.56W (2C) (1799 MSL + 300 ROC = 2099 (2100 MDA), CAT B: 1886 TREE (47-048807) 355316.08N/0844222.37W (1B) (1886 MSL + 300 ROC = 2186 (2200 MDA). CAT C: 1959 TREE 355301.52N/0844227.83W (2C) (1959 MSL + 300 ROC = 2259 (2260 MDA), CAT D: 2480 AAO 355725.43N/0844521.59W (2C) (2480 MSL + 300 ROC = 2780 MDA). RADII: CAT A 1.32, CAT B 1.86, CAT C 2.94, CAT D 3.85. ORDER 8260.3, CHAPTER 2, NEW CIRCLING CRITERIA APPLIED.

Last Updated By: Rafael A Martinez

Last Updated At: 2021-06-04 14:58:32.206947

1/9635

Status: Verified

!FDC X/XXXX RKW IAP ROCKWOOD MUNI, ROCKWOOD, TN. RNAV (GPS) RWY 22, AMDT 1A... CIRCLING CAT A MDA 2100/HAA 436, CAT B MDA 2200/HAA 536, CAT C MDA 2260/HAA 596, CAT D MDA 2780/HAA 1116. VIS CAT D 3. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CROSSVILLE ALTIMETER SETTING: INCREASE LPV DA TO 1987 FEET AND VISIBILITY ALL CATS 1/4 SM; INCREASE LNAV/VNAV DA TO 2011 FEET AND VISIBILITY ALL CATS 1/4 SM; INCREASE ALL MDA 80 FEET AND INCREASE LNAV CAT C AND D VISIBILITY 1/4 SM AND CIRCLING CAT C VISIBILITY 1/2 SM. DELETE NOTE: BARO-VNAV AND VDP NA WHEN USING CROSSVILLE ALTIMETER SETTING. CHART NOTE: BARO-VNAV NA WHEN USING CROSSVILLE ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 22, AMDT 1B. 2106041458-PERM

Digitally signed by
DAVID TEFFETELLER
Jun 09, 2021

QUALITY
45
CHECKED