

HOLDREGE, NEBRASKA

AL-5999 (FAA)

FIG

WAAS CH 69301 W36A	APP CRS 003°	Rwy Idg 4701 TDZE 2310 Apt Elev 2314
--	------------------------	---

RNAV (GPS) RWY 36
BREWSTER FLD (HDE)

RNP APCH - GPS.

T Circling NA to Rwy 11 and 29. When local altimeter setting not received, use EAR altimeter setting and increase LPV DA to 2637 feet and all visibilities $\frac{1}{4}$ SM. Increase all MDAs 80 feet, and LNAV visibility Cat C/D $\frac{1}{8}$ SM and Circling visibility Cats C/D $\frac{1}{4}$ SM. VDP NA when using EAR altimeter setting.


MISSED APPROACH:
Climb to 4000 direct
YETUP and hold.

AWOS-3
121.325

DENVER CENTER
132.7 226.675UNICOM
122.8 (CTAF) **L**

MISSED APCH FIX

PROTOTYPE-NOT
FOR NAVIGATION

A circular logo with the text "MSA RW36 25 NM" curved along the top edge. In the center, there is a small square containing the number "4600" and a circular icon with a crosshair-like pattern.

ELEV 2314		TDZE 2310
-----------	--	-----------

TDZE 2310

4 NM Holding Pattern

(190°T)

6000 ← 183°

3900 → 003°

(010°T)

GP 3.00°

TCH 40

BULLA

KAASE

1.3 NM to RW36

RW36

4000

YETUP

6.1 NM

2.5 NM

1.3 NM

CATEGORY	A	B	C	D
LPV DA	2560-1 250 (300-1)			
LNAV MDA	2760-1 450 (500-1)	2760-1 $\frac{3}{8}$ 450 (500-1 $\frac{3}{8}$)		
CIRCLING	2840-1 526 (600-1)	2880-1 566 (600-1)	3020-2 706 (800-2)	3020-2 $\frac{1}{4}$ 706 (800-2 $\frac{1}{4}$)

HOLDREGE, NEBRASKA

Orig-B FIG

40°27'N-99°20'W

BREWSTER FLD (HDE)

RNAV (GPS) RWY 36