

FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
RIKKK	FIVE	RIKKK5.FISAR	FOUR	08/08/2018	
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

DP ROUTE DESCRIPTION: DENVER INTL:

TAKEOFF RWY 8: CLIMB ON HEADING 082.53 TO INTERCEPT COURSE 065.90 TO CROSS LASSS AT OR BELOW 10000, THEN ON TRACK 024.35 TO SPYCE, THEN ON TRACK 353.50 TO TURBN, THEN ON TRACK 315.84 TO CROSS CHICN AT OR ABOVE 14000, THEN ON TRACK 316.57 TO CROSS FAARM AT OR ABOVE 16000, THEN ON TRACK 331.57 TO RIKKK. THENCE ...

TAKEOFF RWY 16L: CLIMB ON HEADING 172.51 TO 5934, THEN RIGHT TURN DIRECT TO CROSS MUGBE AT OR BELOW 10000, THEN ON TRACK 319.96 TO WAZEE, THEN ON TRACK 354.86 TO LODOE, THEN ON TRACK 029.62 TO CROSS RINKR AT OR ABOVE 14000, THEN ON TRACK 001.30 TO CROSS HERDR AT OR ABOVE 16000, THEN ON TRACK 347.46 TO RIKKK. THENCE ...

TAKEOFF RWY 16R: CLIMB ON HEADING 172.51 TO 5934, THEN RIGHT TURN DIRECT TO CROSS MUGBE AT OR BELOW 10000, THEN ON TRACK 319.96 TO WAZEE, THEN ON TRACK 354.86 TO LODOE, THEN ON TRACK 029.62 TO CROSS RINKR AT OR ABOVE 14000, THEN ON TRACK 001.30 TO CROSS HERDR AT OR ABOVE 16000, THEN ON TRACK 347.46 TO RIKKK. THENCE ...

TAKEOFF RWY 17L: CLIMB ON HEADING 172.54 TO INTERCEPT COURSE 125.33 TO CROSS GISTT AT OR ABOVE 7000, THEN ON TRACK 065.00 TO CROSS KIDNG AT OR BELOW 10000, THEN ON TRACK 355.43 TO SPYCE. THEN ON TRACK 353.50 TO TURBN. THEN ON TRACK 315.84 TO CROSS CHICN AT OR ABOVE 14000. THEN ON TRACK 316.57 TO CROSS FAARM AT OR ABOVE 16000, THEN ON TRACK 331.57 TO RIKKK. THENCE ...

TAKEOFF RWY 17R: CLIMB ON HEADING 172.53 TO INTERCEPT COURSE 118.45 TO CROSS GISTT AT OR ABOVE 7000, THEN ON TRACK 065.00 TO CROSS KIDNG AT OR BELOW 10000, THEN ON TRACK 355.43 TO SPYCE, THEN ON TRACK 353.50 TO TURBN. THEN ON TRACK 315.84 TO CROSS CHICN AT OR ABOVE 14000, THEN ON TRACK 316.57 TO CROSS FAARM AT OR ABOVE 16000, THEN ON TRACK 331.57 TO RIKKK. THENCE ...

TAKEOFF RWY 25: CLIMB ON HEADING 262.51 TO INTERCEPT COURSE 293.70 TO CROSS MUGBE AT OR BELOW 10000, THEN ON TRACK 319.96 TO WAZEE, THEN ON TRACK 354.86 TO LODOE, THEN ON TRACK 029.62 TO CROSS RINKR AT OR ABOVE 14000, THEN ON TRACK 001.30 TO CROSS HERDR AT OR ABOVE 16000, THEN ON TRACK 347.46 TO RIKKK. THENCE ...

TAKEOFF RWY 34L: CLIMB ON HEADING 352.51 TO INTERCEPT COURSE 004.97 TO CROSS CAAZZ AT OR BELOW 10000, THEN ON TRACK 340.59 TO CROSS BNITA AT OR ABOVE 12000, THEN ON TRACK 340.63 TO CROSS SWYCH AT OR ABOVE 16000, THEN ON TRACK 340.59 TO RIKKK. THENCE ...

TAKEOFF RWY 34R: CLIMB ON HEADING 352.51 TO INTERCEPT COURSE 001.98 TO CROSS CAAZZ AT OR BELOW 10000, THEN ON TRACK 340.59 TO CROSS BNITA AT OR ABOVE 12000, THEN ON TRACK 340.63 TO CROSS SWYCH AT OR ABOVE 16000, THEN ON TRACK 340.59 TO RIKKK. THENCE ...

TAKEOFF RWY 35L: CLIMB ON HEADING 352.53 TO 5934, THEN LEFT TURN DIRECT CAAZZ AT OR BELOW 10000, THEN ON TRACK 340.59 TO CROSS BNITA AT OR ABOVE 12000, THEN ON TRACK 340.63 TO CROSS SWYCH AT OR ABOVE 16000, THEN ON TRACK 340.59 TO RIKKK. THENCE ...

TAKEOFF RWY 35R: CLIMB ON HEADING 352.54 TO 5934, THEN LEFT TURN DIRECT CAAZZ AT OR BELOW 10000, THEN ON TRACK 340.59 TO CROSS BNITA AT OR ABOVE 12000, THEN ON TRACK 340.63 TO CROSS SWYCH AT OR ABOVE 16000, THEN ON TRACK 340.59 TO RIKKK. THENCE ...

... THEN ON DEPICTED ROUTE TO FISAR. MAINTAIN FL230 OR FILED LOWER ALTITUDE. EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

CENTENNIAL:

TAKEOFF RWY 17L, 17R: CLIMB ON HEADING 169.95 TO 6400, THEN CONTINUE CLIMB ON HEADING 169.95 OR AS ASSIGNED BY ATC. THENCE ...

TAKEOFF RWY 35L, 35R: CLIMB ON HEADING 349.95 TO 6400, THEN CONTINUE CLIMB ON HEADING 349.95 OR AS ASSIGNED BY ATC. THENCE ...

... RADAR VECTORS TO RIKKK, THEN AS DEPICTED. MAINTAIN FL230 OR FILED LOWER ALTITUDE, EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
RIKKK	FIVE	RIKKK5.FISAR	FOUR	08/08/2018	

ROCKY MOUNTAIN METROPOLITAN:

TAKEOFF RWY 12L, 12R: CLIMB ON HEADING BETWEEN 150 CCW 350 AS ASSIGNED BY ATC. THENCE ...

TAKEOFF RWY 30L, 30R: CLIMBING RIGHT TURN HEADING BETWEEN 350 CW 113 AS ASSIGNED BY ATC. THENCE ...

... RADAR VECTORS TO RIKKK, THEN AS DEPICTED. MAINTAIN FL230 OR FILED LOWER ALTITUDE, EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

NORTHERN COLORADO RGNL:

TAKEOFF RWY 15: CLIMB ON HEADING BETWEEN 180 CCW 350 AS ASSIGNED BY ATC. THENCE ...

TAKEOFF RWY 33: CLIMBING RIGHT TURN HEADING BETWEEN 350 CW 150 AS ASSIGNED BY ATC. THENCE ...

... RADAR VECTORS TO RIKKK, THEN AS DEPICTED. MAINTAIN FL230 OR FILED LOWER ALTITUDE, EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

COLORADO AIR AND SPACE PORT:

TAKEOFF RWY 8: CLIMB ON HEADING 083.15 TO 6020, THEN CONTINUE CLIMB ON HEADING 083.15 OR AS ASSIGNED BY ATC. THENCE ...

TAKEOFF RWY 17: CLIMB ON HEADING 171.99 TO 6020, THEN CONTINUE CLIMB ON HEADING 171.99 OR AS ASSIGNED BY ATC. THENCE ...

TAKEOFF RWY 26: CLIMB ON HEADING 263.17 TO 6020, THEN CONTINUE CLIMB ON HEADING 263.17 OR AS ASSIGNED BY ATC. THENCE ...

TAKEOFF RWY 35: CLIMB ON HEADING 351.99 TO 6020, THEN CONTINUE CLIMB ON HEADING 351.99 OR AS ASSIGNED BY ATC. THENCE ...

... RADAR VECTORS TO RIKKK, THEN AS DEPICTED. MAINTAIN FL230 OR FILED LOWER ALTITUDE, EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	-------------------------------------	----------------------------	--------------------------	---------------	-----------------	------------	-------------	------------------------------------

PROCEDURAL DATA NOTES:

NOTE: DME/DME/IRU OR GPS REQUIRED.

NOTE: RNAV 1.

NOTE: TURBOJETS ONLY.

NOTE: ACCELERATE TO AT OR ABOVE 250 KNOTS ABOVE 10000. IF SLOWER SPEED IS REQUIRED TO MEET CROSSING RESTRICTIONS ADVISE CLNC DEL PRIOR TO TAXI.

NOTE: DENVER INTL AIRPORT-TAKEOFF RWY 8, 16L, 16R, 17L, 17R, 25, 34L, 34R, 35L, 35R - RADAR REQUIRED FOR NON-GPS EQUIPPED AIRCRAFT.

NOTE: CENTENNIAL AIRPORT, ROCKY MOUNTAIN METROPOLITAN AIRPORT, NORTHERN COLORADO RGNL AIRPORT AND COLORADO AIR AND SPACE PORT AIRPORT - RADAR REQUIRED.

TAKEOFF MINIMUMS:

DENVER INTL:

RWYS 7, 26: - NA: ATC.

RWY 8: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 8000, THEN 285 FT PER NM TO 15000.

RWY 16L: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 7000, THEN 260 FT PER NM TO 16000.

RWY 16R: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 7000, THEN 260 FT PER NM TO 16000.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
RIKKK	FIVE	RIKKK5.FISAR	FOUR	08/08/2018	

RWY 17L: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 7000, THEN 220 FT PER NM TO 15000.
RWY 17R: STANDARD WITH MINIMUM CLIMB OF 455 FT PER NM TO 6500, THEN 220 FT PER NM TO 15000.
RWY 25: STANDARD WITH MINIMUM CLIMB OF 425 FT PER NM TO 8000, THEN 270 FT PER NM TO 16000.
RWY 34L: STANDARD WITH MINIMUM CLIMB OF 425 FT PER NM TO 7000, THEN 260 FT PER NM TO 12000.
RWY 34R: STANDARD WITH MINIMUM CLIMB OF 430 FT PER NM TO 7000, THEN 260 FT PER NM TO 12000.
RWY 35L: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 7000, THEN 250 FT PER NM TO 12000.
RWY 35R: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 7000, THEN 250 FT PER NM TO 12000.

CENTENNIAL:

RWY 10, 28: NA - ATC.
RWY 35L, 35R: STANDARD.
RWY 17L: STANDARD WITH MINIMUM CLIMB OF 255 FT PER NM TO 8000.
RWY 17R: STANDARD WITH MINIMUM CLIMB OF 370 FT PER NM TO 8000.

ROCKY MOUNTAIN METROPOLITAN:

RWY 3, 21: NA - ATC.
RWY 12L, 12R, 30L, 30R: STANDARD.

NORTHERN COLORADO RGNL:

RWY 6, 24: NA - VFR RUNWAY.
RWY 15, 33: STANDARD WITH MINIMUM CLIMB OF 320 FT PER NM TO 12000.

COLORADO AIR AND SPACE PORT:

RWY 8, 17, 26, 35: STANDARD.

TAKEOFF OBSTACLES NOTES:

DENVER INTL:
SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

ROCKY MOUNTAIN METROPOLITAN:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CENTENNIAL:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

NORTHERN COLORADO RGNL:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

COLORADO AIR AND SPACE PORT:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

CENTENNIAL:
RWY 17L: 6559 FT MSL AAO 392953.93N/1045044.26W.
RWY 17R: 6021 FT MSL OBS LIGHT ON BLDG 393302.52N/1045119.43W, 6559 FT MSL AAO 392953.93N/1045044.26W.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

REFERENCE MAG VAR: KDEN 8E EPOCH YR: 2015



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
RIKKK	FIVE	RIKKK5.FISAR	FOUR	08/08/2018	

DME / DME ASSESSMENT: SAT (RNP 2.0).
ALL AIRPORTS - CHART: TOP ALTITUDE: FL230.

PILOT NAVIGATION AREA: 10 NM ARC CENTERED ON RIKKK (IF), CW
FROM: POINT A (BEARING 287 DEGREES TO RIKKK)
TO: POINT B (BEARING 016 DEGREES TO RIKKK)
MINIMUM ALTITUDE - 12000.

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
DENVER INTL (KDEN)	DENVER	CO
CENTENNIAL (KAPA)	DENVER	CO
ROCKY MOUNTAIN METROPOLITAN (KBJC)	DENVER	CO
NORTHERN COLORADO RGNL (KFNL)	FORT COLLINS/LOVELAND	CO
COLORADO AIR AND SPACE PORT (KCFO)	DENVER	CO

COMMUNICATIONS:

DENVER INTERNATIONAL AIRPORT: D-ATIS, CLNC DEL, CPDLC, DEN DEP CON
CENTENNIAL AIRPORT: ATIS, CLNC DEL, DEN DEP CON
ROCKY MOUNTAIN METROPOLITAN: ATIS, CLNC DEL, DEN DEP CON
NORTHERN COLORADO RGNL: DEN DEP CON
COLORADO AIR AND SPACE PORT: ATIS, CLNC DEL, DEN DEP CON, DEN CLNC DEL (WHEN TOWER CLOSED)

FIXES AND/OR NAVAIDS:

REMARKS:

ABBREVIATED AMENDMENT

CLIMB GRADIENTS AT CENTENNIAL OFF RWY 17L, 17R ARE OBSTACLE DRIVEN WITH THE CLIMB TO ALTITUDE DETERMINED BY LOCATION OF 8000 MVA AND PROXIMITY TO HIGHER MVA'S.

NORTHERN COLORADO RGNL CLIMB GRADIENT DRIVEN BY CLOSE PROIMITY TO PNA BOUNDARY.

DENVER INTL CLIMB GRADIENTS ARE FOR FMS ENGAGEMENT AT SPECIFIC LOCATIONS, FOR TRANSITION CROSSING ALTITUDES.

THE AIRLINE INDUSTRY HAS REQUESTED THAT BLOCK ALTITUDES NOT BE PUBLISHED ON THE PROCEDURE, WAIVER ON FILE TO REMOVE AT OR ABOVE ALTITUDES ASSOCIATED WITH CROSS AT OR BELOW ALTITUDES.

ATC HAS REQUESTED TO DEVIATE FROM THE STANDARD NAMING CONVENTION CONTAINED IN FAAO 8260.46. SID NAMES CORRESPOND WITH WAYPOINT NAMES AT OUTER BOUNDARY OF DENVER TRACON/ARTCC AIRSPACE. WAIVER APPROVED AND ON FILE.

KBJC RWY 12L, 12R, 30L, 30R: FLIGHT TRACK DISTANCE TO BRYCC PNA BOUNDARY 58 NM PER ATC.
KAPA RWY 17L, 17R, 35L, 35R: FLIGHT TRACK DISTANCE TO BRYCC PNA BOUNDARY 75 NM PER ATC.
KFNL RWY 15, 33: FLIGHT TRACK DISTANCE TO BRYCC PNA BOUNDARY 32 NM PER ATC.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
RIKKK	FIVE	RIKKK5.FISAR	FOUR	08/08/2018	

KCFO RWY 8, 26, 17, 35: FLIGHT TRACK DISTANCE TO BRYCC PNA BOUNDARY 64 NM PER ATC.
KDEN RWY 8: FLIGHT TRACK DISTANCE TO BRYCC PNA BOUNDARY 52 NM PER ATC.

FLIGHT INSPECTED BY:

PROCESSED IAW AIRCRAFT OPS GRP (AJW-33) MEMO,
10/3/18, SUB: FLIGHT INSPECTION REVIEW NOT REQUIRED

OFFICE SYMBOL:

DATE:

Digitally signed by
ALLAN WILL
Dec 20, 2019

DEVELOPED BY:

PHILLIP BRANDENBURG

Digitally signed by

PHILLIP BRANDENBURG

Dec 18, 2019

OFFICE SYMBOL:

DATE:

AJV-A423

08/19/2019

APPROVED BY:

MARLON ROBINSON

OFFICE SYMBOL:

DATE:

AJV-A420

Digitally signed by
ALLAN WILL
Dec 20, 2019

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

A4A	ALPA	AOPA	APA	HAI	NBAA
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

OTHER:

ZDV, BJC ATCT, DEN APP CON, CO AERO MGR, AMGR'S

CHANGES - REASONS:

1. CHANGED ALL AIRPORT NAME REFERENCES FROM FRONT RANGE TO COLORADO AIR AND SPACE PORT, ID CHANGED FROM KFTG TO KCFO - PER FPT/APT REQUEST.

12/10/19: THIS IS A CORRECTED COPY OF THE FORM APPROVED ON 12/4/19.

1. 8260-15B, FIXES AND/OR NAVAIDS: REMOVED TAYOT.

12/18/19: THIS IS A CORRECTED COPY OF THE FORM APPROVED ON 12/4/19.

1. 8260-15B, CHANGED ROCKY MOUNTAIN METROPOLITAN DP ROUTE DESCRIPTION FROM ...EXPECT HIGHER ALTITUDE 10 MINUTES... TO ...EXPECT HIGHER FILED ALTITUDE 10 MINUTES...
2. CHANGED KFTG TO KCFO IN REMARKS.

QUALITY
23
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
RIKKK		FIVE		RIKKK5.FISAR		FOUR		08/08/2018	
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
DENVER INTL		(KDEN)							
RW08 (AER)	395239.20N/1043944.03W	N	-	-	-	-			CG 400 FT PER NM TO 8000 THEN CG 285 FT PER NM TO 15000
	395237.17N/1043505.35W	-	-	VI	090.53	3.58			
LASSS	395439.55N/1042553.19W	Y	FB	CF	073.90	7.37	AT/BELOW 10000		RECOMMENDED NAVAID: DENVER VOR/DME
SPYCE	395816.57N/1042254.52W	Y	FB	TF	032.35	4.28			
TURBN	400321.45N/1042244.14W	Y	FB	TF	001.50	5.08			
CHICN	401131.87N/1043031.80W	Y	FB	TF	323.84	10.12	AT/ABOVE 14000		
FAARM	401828.80N/1043659.40W	Y	FB	TF	324.57	8.53	AT/ABOVE 16000		
RIKKK	404704.36N/1045100.71W	Y	FB	TF	339.57	30.51			
RW16L (AER)	395349.33N/1044112.50W	N	-	-	-	-			CG 400 FT PER NM TO 7000 THEN CG 260 FT PER NM TO 16000
5934 MSL	-	-	-	VA	180.51	-			
MUGBE	395437.37N/1045408.28W	Y	FB	DF	-	-	AT/BELOW 10000		
WAZEE	395810.17N/1045701.43W	Y	FB	TF	327.96	4.18			
LODOE	400459.71N/1045634.81W	Y	FB	TF	002.86	6.83			
RINKR	401157.47N/1044934.69W	Y	FB	TF	037.62	8.79	AT/ABOVE 14000		
HERDR	401858.94N/1044804.48W	Y	FB	TF	009.30	7.11	AT/ABOVE 16000		
RIKKK	404704.36N/1045100.71W	Y	FB	TF	355.46	28.16			
RW16R (AER)	395344.87N/1044145.90W	N	-	-	-	-			CG 400 FT PER NM TO 7000 THEN CG 260 FT PER NM TO 16000
5934 MSL	-	-	-	VA	180.51	-			
MUGBE	395437.37N/1045408.28W	Y	FB	DF	-	-	AT/BELOW 10000		

QUALITY
23
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME							NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
RIKKK							FIVE	RIKKK5.FISAR	FOUR	08/08/2018	
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED		REMARKS	
WAZEE	395810.17N/1045701.43W	Y	FB	TF	327.96	4.18					
LODOE	400459.71N/1045634.81W	Y	FB	TF	002.86	6.83					
RINKR	401157.47N/1044934.69W	Y	FB	TF	037.62	8.79	AT/ABOVE 14000				
HERDR	401858.94N/1044804.48W	Y	FB	TF	009.30	7.11	AT/ABOVE 16000				
RIKKK	404704.36N/1045100.71W	Y	FB	TF	355.46	28.16					
RW17L (AER)	395153.83N/1043828.70W	N	-	-	-	-				CG 400 FT PER NM TO 7000 THEN CG 220 FT PER NM TO 15000	
	394830.48N/1043831.18W	-	-	VI	180.54	3.39					
GISTT	394557.50N/1043501.10W	Y	FB	CF	133.33	3.71	AT/ABOVE 7000			RECOMMENDED NAVAID: DENVER VOR/DME	
KIDNG	394837.67N/1042339.58W	Y	FB	TF	073.00	9.15	AT/BELOW 10000				
SPYCE	395816.57N/1042254.52W	Y	FB	TF	003.43	9.66					
TURBN	400321.45N/1042244.14W	Y	FB	TF	001.50	5.08					
CHICN	401131.87N/1043031.80W	Y	FB	TF	323.84	10.12	AT/ABOVE 14000				
FAARM	401828.80N/1043659.40W	Y	FB	TF	324.57	8.53	AT/ABOVE 16000				
RIKKK	404704.36N/1045100.71W	Y	FB	TF	339.57	30.51					
RW17R (AER)	395140.48N/1043936.56W	N	-	-	-	-				CG 455 FT PER NM TO 6500 THEN CG 220 FT PER NM TO 15000	
	394835.87N/1043938.77W	-	-	VI	180.53	3.07					
GISTT	394557.50N/1043501.10W	Y	FB	CF	126.45	4.44	AT/ABOVE 7000			RECOMMENDED NAVAID: DENVER VOR/DME	
KIDNG	394837.67N/1042339.58W	Y	FB	TF	073.00	9.15	AT/BELOW 10000				
SPYCE	395816.57N/1042254.52W	Y	FB	TF	003.43	9.66					
TURBN	400321.45N/1042244.14W	Y	FB	TF	001.50	5.08					

QUALITY
23

QUALITY
23
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
RIKKK		FIVE		RIKKK5.FISAR		FOUR		08/08/2018	
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
CHICN	401131.87N/1043031.80W	Y	FB	TF	323.84	10.12	AT/ABOVE 14000		
FAARM	401828.80N/1043659.40W	Y	FB	TF	324.57	8.53	AT/ABOVE 16000		
RIKKK	404704.36N/1045100.71W	Y	FB	TF	339.57	30.51			
RW25 (AER)	395026.37N/1044102.17W	N	-	-	-	-			CG 425 FT PER NAM TO 8000 THEN CG 270 FT PER NM TO 16000
	395028.08N/1044523.38W	-	-	VI	270.51	3.35			
MUGBE	395437.37N/1045408.28W	Y	FB	CF	301.70	7.91	AT/BELOW 10000		
WAZEE	395810.17N/1045701.43W	Y	FB	TF	327.96	4.18			
LODOE	400459.71N/1045634.81W	Y	FB	TF	002.86	6.83			
RINKR	401157.47N/1044934.69W	Y	FB	TF	037.62	8.79	AT/ABOVE 14000		
HERDR	401858.94N/1044804.48W	Y	FB	TF	009.30	7.11	AT/ABOVE 16000		
RIKKK	404704.36N/1045100.71W	Y	FB	TF	355.46	28.16			
RW34L (AER)	395106.79N/1044147.72W	N	-	-	-	-			CG 425 FT PER NM TO 7000 THEN CG 260 FT PER NM TO 12000
	395512.13N/1044144.88W	-	-	VI	000.51	4.09			
CAAZZ	400304.52N/1043923.25W	Y	FB	CF	012.97	8.07	AT/BELOW 10000		
BNITA	401720.22N/1044308.73W	Y	FB	TF	348.59	14.54	AT/ABOVE 12000		
SWYCH	404219.21N/1044944.99W	Y	FB	TF	348.63	25.47	AT/ABOVE 16000		
RIKKK	404704.36N/1045100.71W	Y	FB	TF	348.59	4.85			
RW34R (AER)	395150.77N/1044113.88W	N	-	-	-	-			CG 430 FT PER NM TO 7000 THEN CG 260 FT PER NM TO 12000
	395511.56N/1044111.56W	-	-	VI	000.51	3.34			

QUALITY
23
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME							NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
RIKKK							FIVE	RIKKK5.FISAR	FOUR	08/08/2018	
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED		REMARKS	
CAAZZ	400304.52N/1043923.25W	Y	FB	CF	009.98	8.00	AT/BELOW 10000				
BNITA	401720.22N/1044308.73W	Y	FB	TF	348.59	14.54	AT/ABOVE 12000				
SWYCH	404219.21N/1044944.99W	Y	FB	TF	348.63	25.47	AT/ABOVE 16000				
RIKKK	404704.36N/1045100.71W	Y	FB	TF	348.59	4.85					
RW35L (AER)	394941.93N/1043937.98W	N	-	-	-	-				CG 400 FT PER NM TO 7000 THEN CG 250 FT PER NM TO 12000	
5934 MSL	-	-	-	VA	000.53	-					
CAAZZ	400304.52N/1043923.25W	Y	FB	DF	-	-	AT/BELOW 10000				
BNITA	401720.22N/1044308.73W	Y	FB	TF	348.59	14.54	AT/ABOVE 12000				
SWYCH	404219.21N/1044944.99W	Y	FB	TF	348.63	25.47	AT/ABOVE 16000				
RIKKK	404704.36N/1045100.71W	Y	FB	TF	348.59	4.85					
RW35R (AER)	394955.27N/1043830.16W	N	-	-	-	-				CG 400 FT PER NM TO 7000 THEN CG 250 FT PER NM TO 12000	
5934 MSL	-	-	-	VA	000.54	-					
CAAZZ	400304.52N/1043923.25W	Y	FB	DF	-	-	AT/BELOW 1000				
BNITA	401720.22N/1044308.73W	Y	FB	TF	348.59	14.54	AT/ABOVE 12000				
SWYCH	404219.21N/1044944.99W	Y	FB	TF	348.63	25.47	AT/ABOVE 16000				
RIKKK	404704.36N/1045100.71W	Y	FB	TF	348.59	4.85					
RIKKK	404704.36N/1045100.71W	Y	-	IF	-	-					
FISAR	413354.21N/1051410.94W	Y	FB	TF	339.63	49.97					

QUALITY 23

QUALITY
23
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME		NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED		EFFECTIVE DATE		
RIKKK		FIVE		RIKKK5.FISAR		FOUR		08/08/2018				
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS			
CENTENNIAL		(KAPA)										
RW17L (AER)	3935025.91N/1045105.31W	N	-	-	-	-	CG 255 PER NM TO 8000					
6400 MSL	-	-	-	VA	177.95	-						
	-	-	-	VM	177.95	-						
RIKKK	404704.36N/1045100.71W	Y	FB	DF	-	-						
RW17R (AER)	393444.35N/1045113.39W	N	-	-	-	-	CG 370 FT PER NM TO 8000					
6400 MSL	-	-	-	VA	177.95	-						
	-	-	-	VM	177.95	-						
RIKKK	404704.36N/1045100.71W	Y	FB	DF	-	-						
RW35L (AER)	393335.23N/1045110.19W	N	-	-	-	-						
6400 MSL	-	-	-	VA	357.95	-						
		-	-	VM	357.95	-						
RIKKK	404704.36N/105100.71W	Y	FB	DF	-	-						
RW35R (AER)	393324.15N/1045100.76W	N	-	-	-	-						
6400 MSL	-	-	-	VA	357.95	-						
		-	-	VM	357.95	-						
RIKKK	404704.36N/1045100.71W	Y	FB	DF	-	-						
RIKKK	404704.36N/1045100.71W	Y	-	IF	-	-						

QUALITY
23

QUALITY
23
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME		NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED		EFFECTIVE DATE	
RIKKK		FIVE		RIKKK5.FISAR		FOUR		08/08/2018			
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS		
FISAR	413354.21N/1051410.94W	Y	FB	TF	339.63	49.97					
ROCKY MOUTAIN METROPOLITAN		(KBJC)									
RIKKK	404704.36N/1045100.71W	Y	-	IF	-	-					
FISAR	413354.21N/1051410.94W	Y	FB	TF	339.63	49.97					
NORTHERN COLORADO RGNL		(KFNL)									
RIKKK	404704.36N/1045100.71W	Y	-	IF	-	-					
FISAR	413354.21N/1051410.94W	Y	FB	TF	339.63	49.97					
COLORADO AIR AND SPACE PORT		(KCFO)									
RW08 (AER)	394738.42N/1043354.88W	N	-	-	-	-					
6020 MSL	-	-	-	VA	091.15	-					
	-	-	-	VM	091.15	-					
RIKKK	404704.36N/1045100.71W	Y	FB	DF	-	-					
RW17 (AER)	394708.14N/1043127.25W	N	-	-	-	-					
6020 MSL	-	-	-	VA	179.99	-					
	-	-	-	VM	179.99	-					
RIKKK	404704.36N/1045100.71W	Y	FB	DF	-	-					
RW26 (AER)	394736.82N/1043212.43W	N	-	-	-	-					

QUALITY

23

3

QUALITY
23
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME							NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
RIKKK							FIVE	RIKKK5.FISAR	FOUR	08/08/2018	
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED		REMARKS	
6020 MSL	-	-	-	VA	271.17	-					
	-	-	-	VM	271.17	-					
RIKKK	404704.36N/1045100.71W	Y	FB	DF	-	-					
RW35 (AER)	394549.10N/1043127.23W	N	-	-	-	-					
6020 MSL	-	-	-	VA	359.99	-					
	-	-	-	VM	359.99	-					
RIKKK	404704.36N/1045100.71W	Y	FB	DF	-	-					
RIKKK	404704.36N/1045100.71W	Y	-	IF	-	-					
FISAR	413354.21N/1051410.94W	Y	FB	TF	339.63	49.97					

