

[Print](#)

Project Name: KPTT NEW CIRCLING RADII APPLIED

Project Reason: Expanded circling area applied. Secondary altimeter notes updated as required. Only circling visibility verified. Controlling obstacles: CAT A: 2074 TANK (20-023202) 374216.19N/0984427.82W (2C). 2074+300(ROC)=2380 MDA. CAT B: 2079 TREE 374414.80N/0984511.00W (2C). 2079+300(ROC)=2380 MDA. CAT C: 2219 TOWER (20-000174) 373926.00N/0984428.00W (4D). 2219+300(ROC)+50(AC)=2580 MDA. Radii: CAT A: 1.32, CAT B: 1.88, CAT C: 2.95. Order 8260.3, chapter 2, New Circling Criteria Applied.

Last Updated By: James Lafferty

Last Updated At: 2021-04-29 13:59:23.758137

Status: Draft

1/0509

!FDC X/XXXX PTT IAP PRATT RGNL, PRATT, KS. RNAV (GPS) RWY 17, AMDT 1... TDZE 1952. LPV DA 2202/HAT 250 ALL CATS. LNAV/VNAV DA 2257/HAT 305 ALL CATS. LNAV HAT 388 ALL CATS. CIRCLING CAT C MDA 2580/HAA 627, VIS CAT C 1 3/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GREAT BEND ALTIMETER SETTING: INCREASE LPV DA TO 2301 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE LNAV/VNAV DA TO 2356 FEET AND ALL VISIBILITIES 1/2 SM; INCREASE ALL MDAS 100 FEET AND VISIBILITY CAT C 1/4 SM. THIS IS RNAV (GPS) RWY 17, AMDT 1A. 2104291359-PERM

Digitally signed by

DAVID TEFFETELLER

Jun 10, 2021

QUALITY
45
CHECKED