

[Print](#)

Project Name: KSNY NEW CIRCLING RADII APPLIED

Project Reason: Circling updated to new areas. Backup altimeter notes updated based on circling visibility changes and current wording, other visibility values not verified. Controlling obstacles: Cat A/B: Water Tower (31-042874) 410650.05N/1025749.61W 4430 (1A) Cat C: Tower (31-000014) 410309.00N/1025837.90W 4567 (4D) Cat D: Tower (31-000855) 410942.00N/1025958.00W 4601 (5D) Radii: Cat A: 1.38 Cat B: 1.97 Cat C: 3.11 Cat D: 4.08. Order 8260.3, chapter 2, New Circling Criteria Applied

Last Updated By: James Lafferty

Last Updated At: 2020-10-21 13:32:19.786487

Status: Draft **0/6880**

!FDC X/XXXX SNY IAP SIDNEY MUNI/LLOYD W CARR FIELD, SIDNEY, NE. VOR/DME RWY 13, AMDT 5B... CIRCLING CAT C MDA 4920/HAA 607, VIS CAT C 1 3/4. CIRCLING CAT D MDA 4960/HAA 647. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE KIMBALL ALTIMETER SETTING: INCREASE ALL MDAS 160 FEET AND VISIBILITY CATS C AND D 1/2 SM. THIS IS VOR/DME RWY 13, AMDT 5C. 2010211332-PERM

Digitally signed by
DAVID TEFFETELLER
Nov 16, 2020

