

[Print](#)

Project Name: ROW NEW CIR RADII

Project Reason: ORDER 8260.3, CHAPTER 2, NEW CIRCLING CRITERIA APPLIED - CATEGORY RADII: CAT A: 1.36, CAT B: 1.94, CAT C: 3.07 AND CAT D: 4.02. NEW CIRCLING CONTROLLING OBSTACLES: CAT A/B/C: 3824 MSL TANK (35-000344) 331843.00N/1043056.00W (1B) 3824 MSL + 300 ROC = 4124 (4140); CAT D: 3990 MSL AAO 331611.66N/1043657.70W (2C) 3990 MSL + 300 ROC = 4290 (4300). RASS ADJUSTMENT CHANGED FROM 80.5 TO 79.9. REMOVED ADDITIONAL FLIGHT DATA NOTES THAT ARE NO LONGER REQUIRED. UPDATE ALTERNATE MINIMUMS, VISIBILITIES AND NOTES AS REQUIRED.

Last Updated By: Andre Marsh

Last Updated At: 2022-07-22 19:05:24.550436

Status: Verified **2/4382**

!FDC X/XXXX ROW IAP ROSWELL AIR CENTER, ROSWELL, NM. RNAV (GPS) RWY 21, ORIG-B... CIRCLING CAT D MDA 4300/629 HAA. DELETE PROFILE NOTE: *LNAV ONLY. CHANGE VDP FROM *1.3 NM TO RW21 TO 1.3 NM TO RW21. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ARTESIA ALTIMETER SETTING: INCREASE LPV DA TO 3979 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 4075 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE ALL MDAS 80 FEET AND LNAV CAT C/D VISIBILITY 1/8 SM AND CIRCLING CAT D VISIBILITY 1/4 SM. DELETE NOTE: ASR. CHANGE NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING ARTESIA ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 21, ORIG-C. 2207221905-PERM

Digitally signed by
JASON KRETSCHMER
Aug 22, 2022

