

**Federal Aviation  
Administration**

**Transmittal Letter 20-19**

**July 24, 2020**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
9/10/2020	GA	Cordele	Crisp County- Cordele	0/8029	7/15/2020	RNAV (GPS) RWY 10, Amdt 1

**AIRAC Date: 10 SEPTEMBER 2020**

FDC 0/8029 CKF IAP CRISP COUNTY-CORDELE, CORDELE, GA. RNAV (GPS) RWY 10, AMDT 1... CIRCLING CAT A MDA 800/ HAA 490. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ALBANY ALTIMETER SETTING: INCREASE LPV DA TO 708 FEET AND LNAV/VNAV DA TO 822 FEET AND ALL MDA 100 FEET; INCREASE LPV ALL CATS VISIBILITY 1/4 SM, LNAV/VNAV ALL CATS VISIBILITY 1/2 SM, AND INCREASE LNAV CAT C/D AND CIRCLING CAT C/D VISIBILITY 1/4 SM. DELETE NOTE: FOR INOPERATIVE ALS, WHEN USING ALBANY ALTIMETER SETTING: INCREASE LPV CAT A/B VISIBILITY TO 1 3/8 SM; LNAV/VNAV CAT A/B VISIBILITY TO 1 3/4 SM. DELETE NOTE: INOPERATIVE TABLE DOES NOT APPLY TO LNAV CAT A/B WHEN USING ALBANY ALTIMETER SETTING. DELETE NOTE: BARO-VNAV AND VDP NA WHEN USING ALBANY ALTIMETER SETTING. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 10, AMDT 1A. 2007101213-PERM