

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)
2.	HOLD W VNA VORTAC, LT, 079.00 INBOUND, 2100 FT. IN LIEU OF PT (IAF)				
3. FAC	044.24	FAF SAHPS/11.00 DME	DIST FAF TO MAP		THLD 4.57
4. MIN. ALT	SAHPS 1800				
8. MSA FROM:	VNA VORTAC 2600				

EPOCH YEAR:1965

[illegible]

CHART PLANVIEW NOTE: NOPT FOR ARRIVAL ON VNA VORTAC AIRWAY RADIALS 138 CW 299.  
CHART NOTE: USE DUBLIN ALTIMETER SETTING; WHEN NOT RECEIVED, USE MIDDLE GEORGIA RGNL ALTIMETER SETTING AND INCREASE ALL MDA 20 FEET.

FAA FORM 8260-5 / December 2002 (computer generated)