

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.23**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KVCT	<u>PROCEDURE NAME</u> VOR RWY 13	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>CITY</u> VICTORIA	<u>STATE</u> TX		
<u>AIRPORT ELEVATION</u> 115	<u>TDZE</u> 115	<u>SUPERSEDED</u>	<u>ORIGINAL/AMENDMENT</u> NONE	<u>DATED</u>	<u>MAG VAR</u> 6E	<u>EPOCH YEAR</u> 1995
<u>FACILITY</u> VCT	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 12 AUGUST 2021	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
PSX VORTAC		VCT VOR/DME					275.08	36.37	2200

MISSED APPROACH

MAP:

3.22 NM AFTER VCT VOR/DME OR AT VCT 3.22 DME

MISSED APPROACH INSTRUCTIONS:

CLIMBING LEFT TURN TO 2200 DIRECT VCT VOR/DME AND HOLD, CONTINUE CLIMB-IN-HOLD TO 2200.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT L SIDE OF COURSE 306.80 OUTBOUND 2200 FT WITHIN 15 MILES OF VCT VOR/DME (IAF)

2.

3. FAC: 126.80 FAF: VCT VOR/DME DIST FAF TO MAP: 3.22 DIST FAF TO THLD: 3.22

4. MIN ALT: VCT VOR/DME 1300

8. MSA FROM: VCT VOR/DME 2200

EQUIPMENT REQUIREMENTS NOTES:

NOTES:

CHART NOTE: VDP NA WHEN USING PORT LAVACA ALTIMETER SETTING.

CHART NOTE: FOR INOPERATIVE ALS, INCREASE CAT C/D/E VISIBILITY TO 1 3/8 SM.

CHART NOTE: FOR INOPERATIVE ALS WHEN USING PORT LAVACA ALTIMETER SETTING, INCREASE CAT E VISIBILITY TO 1 5/8 SM

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PORT LAVACA ALTIMETER SETTING AND INCREASE ALL MDAS 60 FEET AND VISIBILITY CAT C AND D 1/4 AND CAT E 1/8 SM.



ADDITIONAL FLIGHT DATA:

HOLD NW, RT, 126.80 INBOUND.
CHART FAS OBST: 347 TOWER (48-030725) 285217N/0965804W.
CHART VDP AT 1.99 DME
DISTANCE VDP TO THLD 1.23 NM.
CHART CIRCLING ICON.
VCT VOR/DME TO RW13: 3.31/53.

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD - CAT D 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE.

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
S-13	600	1/2	485	600	1/2	485	600	1	485	600	1	485	600	1	485
CIRCLING	600	1	485	600	1	485	820	2	705	880	2 1/2	765	NA	NA	NA

CHANGES - REASONS

COORDINATED WITH:

A4A ☒ ALPA ☒ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ZHU, VCT ATCT, AMGR

FLIGHT CHECKED BY

THOMAS CONKLIN

Digitally signed by

DONALD H LANIER

Jun 30, 2021

OFFICE

FICO

DATE

06/29/2021

DEVELOPED BY

DONALD H. LANIER (MATTHEW FULKS)

Digitally signed by

DONALD H LANIER

Jun 30, 2021

OFFICE

AJV-A431

DATE

04/15/2021

APPROVED BY

LONNIE EVERHART

Digitally signed by

DONALD H LANIER

Jun 30, 2021

OFFICE

AJV-A430

DATE

TITLE

MANAGER

