

<b>RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.			
TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE	<b>LNAV: RW35</b>  <b>CLIMB TO 2500 DIRECT PPENS AND HOLD.</b>  <b>ADDITIONAL FLIGHT DATA:</b> HOLD N, RT, 168.26 INBOUND. FAS OBST: 709 AAO 300602N/0965804W IYAHE TO RW35: 3.04/43.			
CRAYS	POYLU (FB)	074.63 / 20.04	2600				
JAYJO	IWOKU (FB)	180.82 / 20.98	2500				
IDU VORTAC	IWOKU (FB)	271.26 / 15.79	2500				
POYLU (IAF)	RAMOS (NOPT) (FB)	078.23 / 5.00	2500				
IWOKU (IAF)	RAMOS (NOPT) (FB)	258.33 / 5.00	2500				
RAMOS (IF/IAF)	IYAHE (FB)	348.28 / 6.00	2100				

  

1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF)	
2. HOLD S RAMOS, RT, 348.28 INBOUND, 2500 FT. IN LIEU OF PT (IAF)	
3. FAC: <u>348.28</u> FAF: <u>IYAHE</u>	DIST FAF TO MAP: <u>5.01</u> THLD: <u>5.01</u>
4. MIN. ALT: <u>RAMOS 2500, IYAHE 2100</u>	
5. DIST TO THLD FROM OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u>	
6. MIN GS INCPT: <u>      </u> GS ALT AT: <u>      </u> OM: <u>      </u> MM: <u>      </u> IM: <u>      </u>	
7. GS ANGLE: <u>      </u> TCH: <u>34:1 IS NOT CLEAR</u>	
8. MSA FROM: <u>RW35 2600</u>	

  

MINIMUMS															
TAKEOFF: <u>      </u>	STANDARD <input checked="" type="checkbox"/>	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: <u>NA</u>	STANDARD @										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	960	1	487	960	1	487	960	1 1/4	487		NA				
CIRCLING	960	1	475	960	1	475	960	1 1/2	475		NA				

  

NOTES:

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: PROCEDURE NA AT NIGHT.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AUSTIN-BERGSTROM INTL ALTIMETER SETTING

SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE	ELEVATION: 485 TDZE: 473	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
GIDDINGS, TX	AIRPORT NAME:		RNAV (GPS) RWY 35, ORIG	AMDT: NONE
	GIDDINGS-LEE COUNTY		29 JUL 2010	DATED

TL10-14 Pub 7/29/10