

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.					
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: 3.36 NM AFTER MCW VOR/DME OR AT MCW 3.36 DME FIX					
OZVIQ/MCW 7.00 DME CCW (IAF)		OYKUG/MCW 7.00 DME (NOPT)			7.00 DME ARC (MCW LR-193)			3000		CLIMB TO 2500 THEN CLIMBING LEFT TURN TO 3000 DIRECT MCW VOR/DME AND HOLD.					
HUKAN/MCW 7.00 DME CW (IAF)		OYKUG/MCW 7.00 DME (NOPT)			7.00 DME ARC (MCW LR-159)			3000							
OYKUG/MCW 7.00 DME (IF)		MCW VOR/DME			355.64 / 7.00			2300							
										ADDITIONAL FLIGHT DATA: HOLD S, RT, 356.00 INBOUND. CHART FAS OBST: 1367 POLE 430601N/0932019W CHART VDP AT 2.11 DME DISTANCE VDP TO THLD 1.25 NM. CHART MCW R-278 AT OZVIQ. CHART MCW R-075 AT HUKAN. MCW TO RW36: 2.93/62.					
1. PT <u>L</u> SIDE OF COURSE <u>175.64</u> OUTBOUND <u>2800</u> FT WITHIN <u>10</u> MILES OF <u>MCW VOR/DME</u> (IAF)															
2.															
3. FAC <u>355.64</u> FAF <u>MCW VOR/DME</u> DIST FAF TO MAP <u>3.36</u> THLD <u>3.36</u>															
4. MIN. ALT <u>MCW VOR/DME 2300</u>															
8. MSA FROM: <u>MCW VOR/DME 355-085 3800, 085-355 2800</u>										MAG VAR: 6E EPOCH YEAR: 1965					
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @			
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-36	1640	3/4	447	1640	3/4	447	1640	7/8	447	1640	7/8	447			
CIRCLING	1660	1	446	1680	1	466	1760	1 1/2	546	1780	2	566			
NOTES:															
CHART NOTE: VDP NA WITH CHARLES CITY ALTIMETER SETTING.										@ NA WHEN LOCAL WEATHER NOT AVAILABLE.					
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHARLES CITY ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET AND INCREASE S-36 CAT C/D AND CIRCLING CAT C VISIBILITY 1/4 MILE.															
CITY AND STATE MASON CITY, IA		ELEVATION: 1214 AIRPORT NAME:  MASON CITY MUNI		TDZE: 1193		FACILITY IDENTIFIER: MCW		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 36, AMDT 6F 10 NOVEMBER 2016				SUP AMDT DATE		24 6E 10/15/2015	