

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
UNCAP/AUG 11.00 DME	AUG VOR/DME	166.00 / 11.00	3000	MAP: AUG VOR/DME CLIMB TO 1200 ON AUG VOR/DME R-346 THEN CLIMBING LEFT TURN TO 2300 DIRECT AUG VOR/DME AND HOLD, OR AS DIRECTED BY ATC. ALTERNATE MA: CLIMB TO 3000 ON AUG VOR/DME R-346 TO UNCAP/11.00 DME AND HOLD (DME REQUIRED). ADDITIONAL FLIGHT DATA: HOLD N, RT, 166.00 INBOUND. CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD N UNCAP/11.00 DME, RT, 166.00 INBOUND. CHART FAS OBST: 582 TREE 441802N/0694747W DACCI TO RW35: 3.00/46. FAC 163R OF RWY C/L EXTENDED 3000 FROM THLD.

1. PT L SIDE OF COURSE 174.00 OUTBOUND 2200 FT WITHIN 10 MILES OF AUG VOR/DME (IAF)
 2. _____
 3. FAC 354.00 FAF _____ DIST FAF TO MAP _____ THLD _____
 4. MIN. ALT DACCI/2.50 DME 1100
 8. MSA FROM: AUG VOR/DME 045-225 2600, 225-045 3100

MAG VAR: 18W

EPOCH YEAR: 1985

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-35	1100	1	753	1100	1 1/4	753	1100	2	753	1100	2	753			
CIRCLING	1100	1	748	1100	1 1/4	748	1100	2 1/4	748	1100	2 1/2	748			
DACCI FIX MINIMUMS															
S-35	840	1	493	840	1	493	840	1 3/8	493	840	1 3/8	493			
CIRCLING	960	1	608	980	1	628	980	1 3/4	628	980	2	628			

NOTES:

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED USE WATERTVILLE ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET; INCREASE S-35 CATS C AND D VISIBILITY 1/2 MILE, INCREASE CIRCLING CAT C VISIBILITY 1/4 MILE, INCREASE DACCI FIX MINIMUMS S-35 CATS C AND D VISIBILITY 1/8 MILE.
 (SEE FORM 8260-10)

@ CAT C 800-2 1/4, CAT D 800-2 1/2
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
6
CHECKED

CITY AND STATE AUGUSTA, ME	ELEVATION: 352 THRE: 347 AIRPORT NAME: AUGUSTA STATE	FACILITY IDENTIFIER: AUG	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 35, AMDT 6 05 MAY 2011	SUP AMDT 5A DATE 01/18/2007
--------------------------------------	--	------------------------------------	---	---

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):**CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 35 PROCEDURE NA AT NIGHT.****CHART NOTE: CIRCLING TO RWY 8 AND 26 NA AT NIGHT.**

QUALITY
6
CHECKED

CITY AND STATE

AUGUSTA, ME

ELEVATION: 352

THRE: 347

AIRPORT NAME:

AUGUSTA STATE

FACILITY
IDENTIFIER:

AUG

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 35, AMDT 6

05 MAY 2011

SUP:

AMDT: 5A

DATED: 01/18/2007