

U.S. DEPARTMENT OF TRANSPORTATION — FEDERAL AVIATION ADMINISTRATION
VOR STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - FAR PART 97. 23

Bearings, headings, courses and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALT	MAP: RQZ R-010/15.6
RQZ VORTAC (IAF)	RQZ 5.6 DME	010/5.6	3000	Climb to 2000 then climbing left turn to 3000 via RQZ R-010 to JOYER INT and hold.
RQZ 5.6 DME	JOYER/10.6 DME	010/5	2200	
				ADDITIONAL FLIGHT DATA Hold S, RT, 010 inbound. FAS Obst: 1139 Power Line 350237/863337

- PT NA SIDE OF CRS _____ OUTBND _____ FT WITHIN _____ MI. OF _____ (IAF)
- Profile Starts at RQZ VORTAC (IAF)
- FAC 010 FAF JOYER/RQZ 10.6 DME DIST FAF TO: MAP _____ THLD 5
- MIN ALT RQZ VORTAC 4000, RQZ 5.6 DME 3000, JOYER 2200
- MSA FROM RQZ VORTAC 3700

VAR 2E YR 65

MINIMUMS

TAKEOFF: <input checked="" type="checkbox"/> STD <input type="checkbox"/> SEE FAA FORM 8260-15 FOR THIS AIRPORT	ALTERNATE: <input checked="" type="checkbox"/> NA														
CAT. →	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-01	1400	1	427	1400	1	427	1400	1 1/2	427	1400	1 1/2	427			
Circling	1420	1	436	1440	1	456	1440	1 1/2	456	1540	2	556			

HUNTSVILLE ALTIMETER SETTING MINIMUMS

S-01	1500	1	527	1500	1	527	1500	1 1/2	527	1500	1 3/4	527			
Circling	1540	1	556	1540	1	556	1540	1 1/2	556	1540	2	556			

NOTES

Obtain local altimeter setting on CTAF, when not received use Huntsville altimeter setting.

THIS IS A CORRECTED COPY OF A PROCEDURE PUBLISHED IN TL 91-22.

CITY AND STATE	ELEVATION 984	TDZE 973	FACILITY IDENT.	PROC. NO.-AMDT. NO.-EFFECTIVE DATE	SUP.
Fayetteville, TN	Fayetteville Municipal	RQZ	VOR/DME Rwy 1, Orig	14 NOV 91	AMDT.
					DATED