

U.S. Department
of Transportation

800 Independence Ave., S.W.
Washington D.C. 20591

**Federal Aviation
Administration**

Transmittal Letter 20-09

March 6, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as
follows:

.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/23/2020	MA	Hyannis	Barnstable Muni- Boardman/Polando Field	0/9694	2/26/2020	RNAV (GPS) RWY 33, Orig-B

AIRAC Date: 23 APRIL 2020

FDC 0/9694 HYA IAP BARNSTABLE MUNI-BOARDMAN/POLANDO FIELD, HYANNIS, MA. RNAV (GPS) RWY 33,
ORIG-B... CIRCLING CAT C/D MDA 860/HAA 806. VIS CAT C 2 1/4, CAT D 2 1/2. CHART CIRCLING ICON. CHANGE
NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHATHAM ALTIMETER SETTING:
INCREASE LPV DA TO 332 FEET; INCREASE LNAV/VNAV DA TO 393 FEET; INCREASE ALL MDAS 40 FEET AND
VISIBILITY CATS C AND D 1/4 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT C 900-2 1/4, CAT D 900-2 1/2;
NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 33, ORIG-C. 2002261610-PERM