

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.														
TERMINAL ROUTES											MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW02 CLIMB TO 3000 DIRECT ZESSA AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 200.45 INBOUND. CHART FAS OBST: 1193 BUILDING 404213N/0950300W. DISTANCE TO THLD FROM 250 HAT: 0.66 NM. CHART VDP AT 1.38 NM TO RW02* *LNAV ONLY. WAAS CHANNEL # 99416 REFERENCE PATH ID: W02A CHART CIRCLING ICON. LTP HAE: 271 M									
JOGOL (IF/IAF)		TICTO (TF) (FB) (RNP 1.00)			020.30 / 6.00				2700											
TICTO (FAF)		FAHHO/2.30 NM TO RW02 (TF) (FB) (RNP 0.30)			020.34 / 2.94															
FAHHO/2.30 NM TO RW02		RW02 (MAP) (TF) (FB) (RNP 0.30)			020.34 / 2.30															
RW02 (MAP)		1241 MSL (CA)			020.34				3000											
1241 MSL		ZESSA (DF) (FO) (RNP 1.00)																		
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S JOGOL, RT, 020.30 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 020.34 FAF: TICTO DIST FAF TO MAP: 5.24 THLD: 5.24 4. MIN. ALT: JOGOL 3000, TICTO 2700, FAHHO/2.30 NM TO RW02 1760* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2700 GS ALT AT: TICTO 2700 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 40.0 20:1 IS CLEAR 34:1 IS NOT CLEAR 8. MSA FROM: _____																	MAG VAR: 4E		EPOCH YEAR: 1995	
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT											ALTERNATE: N A		STANDARD @							
CATEGORY =====>		A			B			C			D			E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA					
LPV DA	1241	1	250	1241	1	250	1241	1	250	1241	1	250								
LNAV/VNAV DA	1489	1 3/8	498	1489	1 3/8	498	1489	1 3/8	498	1489	1 3/8	498								
LNAV MDA	1460	1	469	1460	1	469	1460	1 3/8	469	1460	1 3/8	469								
CIRCLING	1500	1	504	1500	1	504	1780	2 1/4	784	1780	2 1/2	784								
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). @ CAT C 800-2 1/4, CAT D 800-2 1/2 PBN REQUIREMENTS NOTE: RNP APCH. CHART NOTE: CIRCLING NA W OF RWY 02-20. CHART NOTE: CIRCLING NA TO RWYS 13 AND 31. (CONTINUED ON PAGE 2)																				
CITY AND STATE CLARINDA, IA				ELEVATION: 996 TDZE: 991 AIRPORT NAME: SCHENCK FIELD				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 2, AMDT 1 19 JULY 2018				SUP: AMDT: ORIG-C DATED 06/22/2017						



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE { ANGLE}/TCH {FEET}).

CHART NOTE: RWY 2 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

TAA

	FROM	TO	ALT
1.	290/30 CW 110/30 (NOPT)	JOGOL (IF/IAF) (FB)	3000
2.	110/30 CW 290/30	110/15 CW 290/15	3200
	110/15 CW 290/15	JOGOL (IAF) (FO)	3000

QUALITY
24
CHECKED

CITY AND STATE CLARINDA, IA	ELEVATION: 996 TDZE: 991 AIRPORT NAME: SCHENCK FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 2, AMDT 1 19 JULY 2018	SUP:
				AMDT: ORIG-C
				DATED: 06/22/2017

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
24
CHECKED

CITY AND STATE
CLARINDA, IA

ELEVATION: 996 **TDZE: 991**
AIRPORT NAME:
SCHENCK FIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 2, AMDT 1
19 JULY 2018

SUP:
AMDT: **ORIG-C**
DATED: **06/22/2017**

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KICL
RUNWAY	RW02
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W02A
LTP/FTP LATITUDE	404254.6350N
LTP/FTP LONGITUDE	0950150.1180W
LTP/FTP ELLIPSOIDAL HEIGHT	+02710
FPAP LATITUDE	404415.8500N
FPAP LONGITUDE	0950101.7500W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 FD2D7CAE

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+03020
FPAP ORTHOMETRIC HEIGHT	+03020

QUALITY
24
CHECKED

CITY AND STATE CLARINDA, IA	ELEVATION: 996 AIRPORT NAME: SCHENCK FIELD	TDZE: 991 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 2, AMDT 1 19 JULY 2018	SUP:
				AMDT: ORIG-C
				DATED: 06/22/2017