

**Federal Aviation
Administration**

Transmittal Letter 24-19

July 19, 2024

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
9/5/2024	KS	Liberal	Liberal Mid-America Rgnl	4/5595	45453	RNAV (GPS) RWY 17, Orig-B

AIRAC Date: 5 SEPTEMBER 2024

FDC 4/5595 LBL IAP LIBERAL MID-AMERICA RGNL, LIBERAL, KS. RNAV (GPS) RWY 17, ORIG-B... CIRCLING CAT C MDA 3400/HAA 515, VIS 1 1/2. ALTERNATIVE MINIMUMS: STANDARD - CAT D 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING GUY ALTIMETER SETTING. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GUY ALTIMETER SETTING AND INCREASE LPV DA TO 3240 FEET; INCREASE LNAV/VNAV DA TO 3432 FEET AND ALL VISIBILITIES 1/4 SM. INCREASE ALL MDAS 120 FEET AND LNAV VISIBILITY CAT C/D 1/4 SM, AND CIRCLING VISIBILITY CAT C/D 1/4 SM. DELETE NOTE: BARO-VNAV NA WHEN USING GUYMON MUNI ALTIMETER SETTING. DELETE NOTE: VDP NA WHEN USING GUYMON MUNI ALTIMETER SETTING. DELETE PROFILE NOTE: *LNAV ONLY. DELETE ASTERISK FROM MINIMUM ALTITUDE AT ZAPAP 2.70 NM TO RW17 3780. DELETE ASTERISK FROM VDP AT 1.10 NM TO RW17. THIS IS RNAV (GPS) RWY 17, ORIG-C. 2406101212-PERM