

U.S. Department of Transportation
Federal Aviation Administration

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

| TERMINAL ROUTES | | | | | MISSED APPROACH | | | | |
|-----------------|-----------------------------------|---------------------|----------|--|-----------------|--|--|--|--|
| FROM | TO | COURSE AND DISTANCE | ALTITUDE | | | | | | |
| BUYSA WP (IAF) | ACELI/5.00NM TO NONDE WP (TF)(FB) | 132.82/5.61 | 10100 | LNAV: RW13 | | | | | |
| ACELI WP | NONDE WP (TF) (FB) | 132.82/5.00 | 9500 | | | | | | |
| CROIN WP (IAF) | ATUCU/10NM TO NONDE WP (TF)(FB) | 236.52/10.14 | 10300 | CLIMB TO 8000, THEN CLIMBING LEFT TURN TO 10400 DIRECT CROIN WP AND HOLD. | | | | | |
| ATUCU WP | NONDE WP (TF) (FB) | 236.52/10.00 | 9500 | | | | | | |
| NONDE WP | DEGCA/3.25NM TO EPACU WP (TF)(FB) | 142.95/2.75 | 9100 | ADDITIONAL FLIGHT DATA: HOLD E, LT, 255.00 INBOUND FAS OBST: 7024 TREE 351214/1075658 CHART VDP AT 2.52NM TO RW13 EPACU WP TO RW13 3.05/40 FINAL SEGMENT (TF) | | | | | |
| DEGCA WP | EPACU WP (TF) (FB) | 142.95/3.25 | 8600 | | | | | | |
| RW13 (MAP) | 8000 MSL (CA) | 136.94 | | | | | | | |
| 8000 MSL | CROIN WP (DF)(FO) | | 10400 | | | | | | |

1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT NONDE WP
3. FAC: 136.94 FAF: EPACU WP DIST FAF TO MAP: - THLD: 6.24
4. MIN. ALT: NONDE WP 9500, DEGCA/3.25NM TO EPACU WP 9100, EPACU WP 8600
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 34:1 IS NOT CLEAR
8. MSA FROM: RW13 12600

MAG VAR: 11E EPOCH YEAR: 05

| MINIMUMS | | | | | | | | | | | | | | | | |
|----------|----------|-----|--|----------------|-------|---------|--------|-------|---------|--------|-----|---------|--------|-----|---------|--|
| TAKEOFF: | STANDARD | X | SEE FAA FORM 8260-15A FOR THIS AIRPORT | ALTERNATE: N A | X | | | | | | | | | | | |
| CATEGORY | A | | | B | | | C | | | D | | | E | | | |
| | DH/MDA | VIS | HAT/HAA | DH/MDA | VIS | HAT/HAA | DH/MDA | VIS | HAT/HAA | DH/MDA | VIS | HAT/HAA | DH/MDA | VIS | HAT/HAA | |
| LNAV MDA | 7380 | 1 | 843 | 7380 | 1 1/4 | 843 | 7380 | 2 1/2 | 843 | | NA | | | | | |
| CIRCLING | 7380 | 1 | 843 | 7420 | 1 1/4 | 883 | 7480 | 2 3/4 | 943 | | NA | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |

NOTES: IF LOCAL ALTIMETER SETTING NOT RECEIVED, PROCEDURE NA.
GPS OR RNP -0.3 REQUIRED. DME/DME RNP -0.3 NA.
CIRCLING NA E OF RWYS 13 - 31.
PROCEDURE NA AT NIGHT.

| | | | | |
|----------------|--------------------------------------|----------------------|--|------------|
| CITY AND STATE | ELEVATION: 6537 TDZE: 6537 | FACILITY IDENTIFIER: | PROCEDURE NO./AMDT NO./EFFECTIVE DATE: | SUP: |
| GRANTS, NM | AIRPORT NAME: GRANTS-MILAN MUNICIPAL | RNAV | OCT 30 2003 RNAV (GPS) RWY 13, ORIG | AMDT: NONE |
| | | | | DATE |