

U.S. Department of Transportation Federal Aviation Administration		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW14 CLIMB TO 3600 DIRECT HOVIR AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE HOVIR, RT, 322.24 INBOUND CHART FAS OBST: 1435 TOWER 321358N/0981054W, 1564 TREE 321800N/0981330W ROUTE TYPE DESCRIPTION: A, P APPROACH ROUTE QUALIFIER 2: S CHART VDP AT 1.42 MILES TO RW14 HAVUS TO RW14: 3.05/40 MAG VAR: 7E EPOCH YEAR: 90											
ORBEE (IAF) (40E) (43A)	WOGAN (NOPT) (TF) (FB) (40E) (41E) (43B)	232.16/5.00	3600												
ZEBUN (IAF) (40E) (43A)	WOGAN (NOPT) (TF) (FB) (40E) (41E) (43B)	052.07/5.00	3600												
WOGAN (IF/IAF) (40E) (43I)	HAVUS (TF) (FB) (40E) (43F)	142.11/6.01	3000												
RW14 (MAP) (40G) (41Y) (43M)	1721 MSL (CA) (42M)	142.14													
1721 MSL	HOVIR (DF)(FO) (40E) (41E) (43H)		3600												
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NW WOGAN, RT, 142.11 INBOUND, 3600 FT IN LIEU OF PT (IAF)(40E)(41E)(43C) 3. FAC: <u>142.14</u> FAF: <u>HAVUS</u> DIST FAF TO MAP: <u>5.07</u> THLD: <u>5.07</u> 4. MIN. ALT: <u>WOGAN 3600, HAVUS 3000, FOLON/2.10 NM TO RW14 (40E)(42S) 1960</u> 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: <u>34:1</u> IS NOT CLEAR 8. MSA FROM: _____															
MINIMUMS															
TAKEOFF:	<input type="checkbox"/> STANDARD	<input checked="" type="checkbox"/> SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A		<input checked="" type="checkbox"/> STANDARD										
CATEGORY =====>	A		B		C										
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV MDA	1820	1	499	1820	1	499	1820	1 1/4	499	1820	1 1/2	499			
CIRCLING	1820	1	499	1820	1	499	1820	1 1/2	499	1960	2	639			
NOTES: CHART NOTE: DME/DME RNP-0.3 NA.															
CITY AND STATE		ELEVATION: 1321 TDZE: 1321		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP:					
STEPHENVILLE, TX		AIRPORT NAME: CLARK FIELD MUNI		RNAV		OCT 27 2005 RNAV (GPS) RWY 14, ORIG				AMDT: NONE					
										DATE					

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV

STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA AREA

FROM	TO	ALTITUDE
1. 052/30 CW 232/30	WOGAN (IF/IAF) (NOPT)	3600
2. 232/30 CW 322/30	ORBEE (IAF)	3600
3. 322/30 CW 052/30	ZEBUN (IAF)	3600

CITY AND STATE

STEPHENVILLE, TX

ELEVATION:

1321 TDZE:

1321

AIRPORT NAME:

CLARK FIELD MUNI

FACILITY

IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

OCT 27 2005

RNAV (GPS) RWY 14, ORIG

SUP:

AMDT:

NONE

DATED: