

U.S. Department  
of Transportation

800 Independence Ave., S.W.  
Washington D.C. 20591

**Federal Aviation  
Administration**

**Transmittal Letter 20-09**

**March 6, 2019**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as  
follows:

.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
4/23/2020	MN	Thief River Falls	Thief River Falls Rgnl	0/5076	2/19/2020	RNAV (GPS) RWY 13, Orig-A

**AIRAC Date: 23 APRIL 2020**

FDC 0/5076 TVF IAP THIEF RIVER FALLS RGNL, THIEF RIVER FALLS, MN. RNAV (GPS) RWY 13, ORIG-A... CIRCLING  
CAT C MDA 1820/HAA 701, CAT D MDA 1980/HAA 861, VIS CAT C 2, CAT D 2 3/4. CHART CIRCLING ICON. DELETE  
NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CROOKSTON ALTIMETER SETTING AND INCREASE  
ALL DA 82 FEET AND ALL MDA 100 FEET, INCREASE LPV ALL CATS VISIBILITY 1/8 MILE, LNAV/VNAV ALL CATS  
VISIBILITY 1/4 MILE, AND INCREASE LNAV CATS C/D VISIBILITY TO 1 3/8 MILE. CHART NOTE: WHEN LOCAL  
ALTIMETER SETTING NOT RECEIVED, USE CROOKSTON ALTIMETER SETTING: INCREASE LPV DA TO 1447 FEET  
AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 1518 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE  
ALL MDAS 100 FEET AND VISIBILITY CATS C AND D 3/8 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D  
900-2 3/4, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 13, ORIG-B. 2002141540-PERM