

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
EHMAN INT	KATHI LOM	274.50 / 21.34	2300	MAP: 4.11 MILES AFTER KATHI LOM
				CLIMBING RIGHT TURN TO 3200 DIRECT KATHI LOM AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3200.
				ADDITIONAL FLIGHT DATA: FAS OBST: 839 AAO 430628N/0785022W CHART CYR 518. KATHI LOM TO RW28R: 3.10/55.0. CHART NIAGARA FALLS FLIGHT RESTRICTION AREA

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD E KATHI LOM, RT, 280.27 INBOUND, 2200 FT. IN LIEU OF PT (IAF)
- FAC 280.41 FAF KATHI LOM DIST FAF TO MAP 4.11 THLD 4.11
- MIN. ALT KATHI LOM 2000
- MSA FROM: IA LOM 115-205 3700, 205-295 2800, 295-115 2400

MAG VAR: 10W EPOCH YEAR: 1985

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-28R	1200	4000	612	1200	4000	612	1200	1 3/8	612	1200	1 3/8	612			
CIRCLING	1200	1	608	1200	1	608	1200	1 3/4	608	1360	2 1/2	768			

NOTES:

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BUFFALO NIAGARA INTL ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET, INCREASE S- 28R CAT C/D VISIBILITY 1/8 MILE AND CIRCLING CAT C/D VISIBILITY 1/4 MILE.
 CHART NOTE: CIRCLING TO RWY 6/24/10R/28L NA AT NIGHT.
 (SEE FORM 8260-10)

- @ CAT D 800-2 1/2
- @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
- @ NA WHEN CONTROL TOWER CLOSED.

QUALITY
4
CHECKED

CITY AND STATE NIAGARA FALLS, NY	ELEVATION: 592 THRE: 588	FACILITY IDENTIFIER: IA	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 28R, AMDT 17 19 SEPTEMBER 2013	SUP NDB OR GPS RWY	
	AIRPORT NAME: NIAGARA FALLS INTL			28R	
	AMDT			16B	
				DATE	05/05/2011

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: FOR INOPERATIVE MALSR, INCREASE S-28R CATS A/B VISIBILITY TO RVR 5500 AND CATS C/D VISIBILITY TO 1 3/4.

CHART NOTE: FOR INOPERATIVE MALSR WHEN USING BUFFALO NIAGARA INTL ALTIMETER SETTING, INCREASE S-28R CATS C/D VISIBILITY TO 1 7/8.

QUALITY
4
CHECKED

CITY AND STATE NIAGARA FALLS, NY	ELEVATION: 592	THRE: 588	FACILITY IDENTIFIER: IA	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 28R, AMDT 17 19 SEPTEMBER 2013	SUP: NDB OR GPS RWY 28R
	AIRPORT NAME: NIAGARA FALLS INTL	AMDT: 16B			
		DATED: 05/05/2011			