

**Federal Aviation  
Administration**

**Transmittal Letter 20-07**

**February 7, 2020**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
3/26/2020	MA	Worcester	Worcester Rgnl	0/5469	1/22/2020	ILS OR LOC RWY 29, Amdt 4C

**AIRAC Date: 26 MARCH 2020**

FDC 0/5469 ORH IAP WORCESTER RGNL, WORCESTER, MA. ILS OR LOC RWY 29, AMDT 4C... CHART CIRCLING ICON. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BEDFORD ALTIMETER SETTING AND INCREASE ALL DA 189 FEET AND ALL MDA 200 FEET; INCREASE S-ILS ALL CATS VISIBILITY TO 1 1/4, INCREASE S-LOC CATS C/D VISIBILITY TO 1 3/4, AND CIRCLING CAT B TO 1 1/4, CAT C TO 2 3/4. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BEDFORD ALTIMETER SETTING AND INCREASE ALL DA 189 FEET AND ALL MDA 200 FEET; INCREASE S-ILS ALL CATS VISIBILITY TO 1 1/4 SM, INCREASE S-LOC CATS C/D VISIBILITY TO 1 3/4 SM, AND CIRCLING CAT B TO 1 1/4 SM. CIRCLING CAT B MDA 1720/HAA 711, CIRCLING CAT C MDA 2000/HAA 991, VIS CAT C 3, CIRCLING CAT D MDA 2000/HAA 991. ALTERNATE MINIMUMS: ILS: STANDARD - NA WHEN LOCAL WEATHER NOT AVAILABLE., NA WHEN CONTROL TOWER CLOSED.; LOC: STANDARD - CAT C, D 1000-3, NA WHEN LOCAL WEATHER NOT AVAILABLE., NA WHEN CONTROL TOWER CLOSED. DELETE NOTE: DME REQUIRED. EQUIPMENT REQUIREMENTS NOTE: DME REQUIRED. THIS IS ILS OR LOC RWY 29, AMDT 4D. 2001211713-PERM