

U.S. Department of Transportation
Federal Aviation Administration

**RNAV STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
MUFIE WP (IAF/IF) RW11 (MAP)	JETVY WP (FB) (TF)	107.90/5.50	1500	LNAV: RW11
	DIRMY WP (FO) (DF)		3000	CLIMBING RIGHT TURN TO 3000 DIRECT DIRMY WP AND HOLD
	ADDITIONAL FLIGHT DATA: HOLD SW, RT 060.56 INBOUND FAS OBST: 358' BLDG 404231/0741207 CHART 379 TREE 404327/0741548 FINAL SEGMENT (TF)			

1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT MUFIE WP
3. FAC: 107.92 FAF: JETVY WP DIST FAF TO MAP: - THLD: 4.50
4. MIN. ALT: MUFIE WP 2000, JETVY WP 1500
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 34:1 IS NOT CLEAR
8. MSA FROM: RW 11 2800

JETVY WP TO RW 11: 2.99/53

MAG VAR: 13W EPOCH YEAR: 85

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15 FOR THIS AIRPORT	ALTERNATE: N A			X								
CATEGORY		A			B			C			D			E		
		DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV	MDA	620	1	602	620	1	602	620	1 3/4	602	620	2	602			
CIRC		660	1	642	660	1	642	660	1 3/4	642	900	3	882			

NOTES: GPS OR RNP-0.3 REQUIRED. DME/DME RNP-0.3 NA.

RADAR REQUIRED

CITY AND STATE	ELEVATION: 18 TDZE: 18	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
NEWARK, NJ	AIRPORT NAME: NEWARK INTL	RNAV	NOV - 1 2001 RNAV (GPS) RWY 11, ORIG	AMDT: NONE
				DATED