

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: SEMKE CLIMBING RIGHT TURN TO 3700 DIRECT ROBUE AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3700. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 436 TREE 623830N/1601124W VEYBU TO RW35: 3.05/35
UYADA (IAF)	ROBUE (NOPT) (FB)	261.50 / 5.00	3700	
TUDUE (IAF)	ROBUE (NOPT) (FB)	081.18 / 5.00	3700	
ROBUE (IF/IAF)	TOYNO (FB)	351.34 / 3.00	2900	
TOYNO	VEYBU (FB)	351.34 / 3.01	2100	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD S ROBUE, RT, 351.34 INBOUND, 3700 FT. IN LIEU OF PT (IAF)
- FAC: 351.36 FAF: VEYBU DIST FAF TO MAP: 4.99 THLD: 5.49
- MIN. ALT: ROBUE 3700, TOYNO 2900, VEYBU 2100
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 15E EPOCH YEAR: 2010

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A	FOR THIS AIRPORT	ALTERNATE: N A		STANDARD @								
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA	700	1	410	700	1	410	700	1 1/4	410	700	1 1/4	410				
CIRCLING	740	1	431	760	1	451	760	1 1/2	451	860	2	551				

NOTES:
CHART NOTE: WHEN VGSI INOP, PROCEDURE NA AT NIGHT.
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE	ELEVATION: 309 TDZE: 290	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO.:	SUP:
ANVIK, AK	AIRPORT NAME:	RNAV	RNAV (GPS) RWY 35, ORIG	AMDT: NONE
	ANVIK		SEP 25 2008	DATED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HOLY CROSS ALTIMETER SETTING AND INCREASE ALL MDAS 120 FEET AND LNAV VISIBILITY CAT C 1/4 MILE, CAT D 1/2 MILE.

TAA

	FROM	TO	ALT
1.	262/30 CW 081/30 (NOPT)	262/8 CW 081/8	4700
2.	262/8 CW 081/8	ROBUE (IF/IAF) (FB)	3700
3.	081/30 CW 171/30	081/17 CW 171/17	4200
4.	081/17 CW 171/17	TUDUE (IAF) (FB)	3700
5.	171/30 CW 262/30	171/19 CW 262/19	4200
6.	171/19 CW 262/19	UYADA (IAF) (FB)	3700

CITY AND STATE

ANVIK, AK

ELEVATION: 309 TDZE: 290

AIRPORT NAME:

ANVIK

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO.:

RNAV (GPS) RWY 35, ORIG

SEP 25 2008

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible]

SUP:	
AMDT:	NONE
DATED:	

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-15

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	ROBUE	ROBUE	010		HF	R	FB		351.3(006T)	004.0	03700
	TUDUE	TUDUE	010	IAF	IF		FB				
	TUDUE	ROBUE	020		TF		FB	1.0	081.2(096T)	005.0	03700
	UYADA	UYADA	010	IAF	IF		FB				
	UYADA	ROBUE	020		TF		FB	1.0	261.5(277T)	005.0	03700
		ROBUE	010	FACF	IF		FB				03700
		TOYNO	011	SDF	TF		FB	0.5	351.3(006T)	003.0	02900
		VEYBU	020	FAF	TF		FB	0.5	351.3(006T)	003.0	02100
		SEMKE	030	MAP	TF		FO	0.3	351.4(006T)	005.0	00485

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
		040		CA		FB	1.0	351.4(006T)		00700
	ROBUE	050		DF	R	FO	1.0			03700
	ROBUE	060		HM	R	FO	2.0	351.3(006T)	004.0	03700

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	ROBUE	N622707.11	W1601414.04	N6227.119	W16014.234
	SEMKE	N623801.09	W1601136.21	N6238.018	W16011.604
	TOYNO	N623005.47	W1601331.18	N6230.091	W16013.520
	TUDUE	N622739.73	W1602456.08	N6227.662	W16024.935
	UYADA	N622633.67	W1600332.40	N6226.561	W16003.540
	VEYBU	N623304.62	W1601248.00	N6233.077	W16012.800
	RW35	N623830.81	W1601128.99	N6238.514	W16011.483

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW35	00290	35

CITY AND STATE
ANVIK, AK

ELEVATION: 309 TDZE: 290
 AIRPORT NAME:
ANVIK

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO.:
RNAV (GPS) RWY 35, ORIG
SEP 25 2008

SUP:
 AMDT: **NONE**
 DATED: